

25YR/72HR STORM ANALYSIS

***** Basin Summary - 2572 *****

Basin Name:	BASIN-3	B-3-PRE
Group Name:	BASE	BASE
Node Name:	POND-3	DUMMY
Hydrograph Type:	UH	UH

Unit Hydrograph:	UH256	UH256
Peaking Factor:	256.00	256.00
Spec Time Inc (min):	1.33	1.33
Comp Time Inc (min):	1.33	1.33
Rainfall File:	SFWMD72	SFWMD72
Rainfall Amount (in):	10.50	10.50
Storm Duration (hr):	72.00	72.00
Status:	ONSITE	ONSITE
Time of Conc. (min):	10.00	10.00
Lag Time (hr):	0.00	0.00
Area (acres):	19.91	19.91
Vol of Unit Hyd (in):	1.00	1.00
Curve Number:	82.00	70.00
DCIA (%):	0.00	0.00

72 HR STORM

Time Max (hrs):	60.02	60.02
Flow Max (cfs):	86.69	76.46
Runoff Volume (in):	8.26	6.67
Runoff Volume (cf):	596697	482314

PEAK ALLOWABLE DISCHARGE

25YR/72HR STORM ANALYSIS


***** Basin Summary - 2572 *****

Basin Name:	BASIN-4	B-4-PRE
Group Name:	BASE	BASE
Node Name:	POND-4	DUMMY
Hydrograph Type:	UH	UH
Unit Hydrograph:	UH256	UH256
Peaking Factor:	256.00	256.00
Spec Time Inc (min):	1.33	1.33
Comp Time Inc (min):	1.33	1.33
Rainfall File:	SFWM72	SFWM72
Rainfall Amount (in):	10.50	10.50
Storm Duration (hr):	72.00	72.00
Status:	ONSITE	ONSITE
Time of Conc. (min):	10.00	10.00
Lag Time (hr):	0.00	0.00
Area (acres):	5.51	5.51
Vol of Unit Hyd (in):	1.00	1.00
Curve Number:	84.00	70.00
DC1A (%):	0.00	0.00
Time Max (hrs):	60.02	60.02
Flow Max (cfs):	24.34	21.16
Runoff Volume (in):	8.51	6.67
Runoff Volume (cf):	170272	133478

72 HR STORM

PEAK ALLOWABLE DISCHARGE

Poinciana Parkway Segments 1, 2, 3
SFWMD ERP App. 141010-12



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

CLAYTON J. LEE, P.E.
P.E. LICENSE NUMBER 44032
DEWBERRY / BOWYER-SINGLETON
520 S. MAGNOLIA AVENUE
ORLANDO, FL 32801
CERTIFICATE OF AUTHORIZATION 8794

OSCEOLA COUNTY EXPRESSWAY AUTHORITY		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
	POLK	

OVERALL DRAINAGE MAP (1)
APPENDIX B, Page 224 of 237

SHEET NO.




REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

CLAYTON J. LEE, P.E.
P.E. LICENSE NUMBER 44032
DEWBERRY / BOWYER-SINGLETON
520 S. MAGNOLIA AVENUE
ORLANDO, FL 32801
CERTIFICATE OF AUTHORIZATION 8794

OSCEOLA COUNTY EXPRESSWAY AUTHORITY		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
	POLK	

POST - DRAINAGE MAP
APPENDIX B, Page 225 of 237

SHEET NO.




REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

CLAYTON J. LEE, P.E.
P.E. LICENSE NUMBER 44032
DEWBERRY / BOWYER-SINGLETON
520 S. MAGNOLIA AVENUE
ORLANDO, FL 32801
CERTIFICATE OF AUTHORIZATION 8794

OSCEOLA COUNTY EXPRESSWAY AUTHORITY		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
	POLK	

POST - DRAINAGE MAP
APPENDIX B, Page 226 of 237

SHEET NO.



REVISIONS			
DATE	DESCRIPTION	DATE	DESCRIPTION

KEVIN E. KNUDSEN, P.E.
P.E. LICENSE NUMBER 41062
DEWBERRY | BOWYER-SINGLETON
520 SOUTH MAGNOLIA AVENUE
ORLANDO, FL 32801
CERTIFICATE OF AUTHORIZATION 8794

OSCEOLA COUNTY EXPRESSWAY AUTHORITY		
ROAD NO.	COUNTY	FINANCIAL PROJECT ID
	OSCEOLA	

POST-DRAINAGE MAP
SEGMENT 3
APPENDIX B, Page 227 of 237

SHEET NO.

**POINCIANA PARKWAY DESIGN / BUILD PROJECT
Osceola and Polk Counties, FL**

CROSS-DRAIN SUMMARY TABLE

Segment	ID	Station	Existing Cross-Drain			Proposed Cross-Drain			ULTIMATE Cross-Drain			Remarks
			Length	Size	DHW	Length	Size	DHW	Length	Size	DHW	
1	CD-1	493+00	63'	6' x 3' CBC	95.61	88'	6' x 3' CBC	95.19				Extend existing CD
1	CD-2	502+10	76'	24" pipe	95.13	122'	24" pipe	95.13				Extend existing CD
2	CD-3	107+60	50'	36" CMP	92.93	148'	36" pipe	92.06				
2	CD-4	129+45	41'	30" CMP	89.59	86'	(2) 24" pipes	89.13	169'	(2) 24" pipes	89.60	
2	CD-4A	140+74	57'	24" RCP	84.37	88'	24" pipe	84.36	156'	24" pipe	84.37	
2	CD-5	152+55	41'	24" RCP	84.33	81'	(2) 24" pipes	83.37	169'	(2) 24" pipes	83.55	
3	CD-6	174+64	20'	24" CMP	77.58	103'	(2) 24"x38" pipes	77.20	170'	(2) 24"x38" pipes	77.23	Use Class IV Pipe and Friable Base (Index 205)
3	CD-7	324+00				145'	(2) 36" pipes	67.02	192'	(2) 36" pipes	67.10	Wetland Equalizer Cross-drains. Use Class IV Pipe and Friable Base (Index 205)
3	CD-8	328+00				145'	(2) 36" pipes	67.02	192'	(2) 36" pipes	67.10	
3	CD-9	340+05				126'	30" pipe	68.09	200'	30" pipe	68.09	Basin W7 to W6 outfall. Use Class IV Pipe and Friable Base (Index 205)

NOTES:
DHW: Design High Water Elevation

F. A. Project No. : 432294-1-58-01
Date : 9/24/2014

STRUCTURE No.	STATION	DESIGN FLOOD		BASE FLOOD		OVERTOPPING FLOOD				GREATEST FLOOD			
		2 % Prob.	50 yr Freq.	1 % Prob.	100 yr Freq.			Prob.	Freq.			Prob.	Freq.
		Discharge	Stage	Discharge	Stage	Discharge	Stage	%	yr	Discharge	Stage	%	yr
CD-1	493+00	135	95.2	151	95.6					257	96.4	0.2	500
CD-2	502+10	24	95.1	26	95.4					45	95.9	0.2	500
CD-3	107+60	53	92.1	59	92.6	77.8	94.3	0.43	231				
CD-4	129+45	37	89.1	41	89.4					70	92.1	0.2	500
CD-4A	140+74	24	84.4	26	84.4					45	84.5	0.2	500
CD-5	152+55	24	83.4	26	83.5					45	84.9	0.2	500
CD-6	174+64	24	77.2	26	77.2					45	77.7	0.2	500
CD-7	324+00	115	67.0	177	68.1					301	71.3	0.2	500
CD-8	328+00	115	67.0	177	68.1					301	71.3	0.2	500
CD-9	340+00	17	68.1	23	68.6					39	70.2	0.2	500

NOTE : The hydraulic data is shown for informational purposes only, to indicate the flood discharges and water surface elevations which may be anticipated in any given year. This data was generated using highly variable factors determined by a study of the watershed. Many judgements and assumptions are required to establish these factors. The resultant hydraulic data is sensitive to changes, particularly of antecedent conditions, urbanization, channelization, and land use. Users of this data are cautioned against the assumption of precision which can not be attained. Discharges are in cubic feet per second (cfs) and stages are in feet (ft), NGVD, 1929.

DEFINITIONS:

- Design Flood : The flood selected by the FDOT to be utilized to assure a standard level of hydraulic performance.
- Base Flood : The flood having a 1 % chance of being exceeded in any year. (100 yr frequency)
- Overtopping Flood : The flood where flow occurs (A) over the highway, (B) over a watershed divide or (C) thru emergency relief structures.
- Greatest Flood : The most severe flood which can be predicted where overtopping is not practicable, normally one with a 0.2 % chance of being exceeded in any year. (500 yr frequency)

Data adapted from : N/A

Prepared By : Kevin Koehler, PE
Date : September 24, 2014

Approved for use
on this project By : _____
Date : _____

PROJECT: POINCIANA PARKWAY
SUBJECT: EXISTING / PROPOSED CULVERT ANALYSIS

CROSSDRAIN CHARACTERISTICS:

CROSS DRAIN NO.		CD-1			
		Existing		Proposed	
LOCATION	STA.	493+00.00		493+00.00	
WIDTH		6.00	FT	6.00	FT
HEIGHT		3.00	FT	3.00	FT
BARRELS		1		1	
DIAMETER		0.00	IN	0.00	IN
LENGTH		62.5	FT	88.0	FT
TOTAL CROSS-SECTIONAL AREA		18.00	SF	18.00	SF
MANNING'S ROUGHNESS		0.012		0.012	
UPSTREAM INVERT		91.00	FT	91.00	FT
DOWNSTREAM INVERT		91.16	FT	90.90	FT
CRITICAL ELEVATION *		95.20	FT	95.20	FT
DETERMINE FLOWRATES (Q):					
ASSUMED VELOCITY (25 YR)	6.00 FT/S	Headwater Elevation		Headwater Elevation	
Q (25 YR) = V (25 YR) * TOTAL AREA	108 CFS	94.81	FT	94.49	FT
Q (50 YR) = 1.25 * Q (25 YR)	135 CFS	95.51	FT	95.19	FT
Q (100 YR) = 1.40 * Q (25 YR)	151 CFS	95.75	FT	95.55	FT
Q (500 YR) = 1.70 * Q (100 YR)	257 CFS	96.51	FT	96.42	FT

NOTES:

- Adjacent Floodplain Limits, SHWT Avg= 91.0 FT
- Survey Adjacent Wetlands, SHWT Avg(East)= 91.3 FT
- Stainline observed at Ex. Conc. Box Culvert = **91.9** FT Down-stream Tailwater used from stainline
- *Surveyed overflow elevation to CD-2 = **95.2** FT
- Low Edge of Travel Lane (496+00) **96.9** FT 50YR DHW is lower

Analysis done with HY-8 Version 7.3 (Jan. 2013)

PROJECT: POINCIANA PARKWAY
SUBJECT: EXISTING / PROPOSED CULVERT ANALYSIS

CROSSDRAIN CHARACTERISTICS:

CROSS DRAIN NO. LOCATION	Existing		CD-4 Proposed		ULTIMATE	
	129+10		129+45		129+45	
WIDTH	0.00	FT	0.00	FT	0.00	FT
HEIGHT	0.00	FT	0.00	FT	0.00	FT
BARRELS	1		2		2	
DIAMETER	30.00	IN	24.00	IN	24.00	IN
LENGTH	41.00	FT	86.00	FT	169.00	FT
TOTAL CROSS-SECTIONAL AREA	4.91	SF	6.28	SF	6.28	SF
MANNING'S ROUGHNESS	0.024		0.012		0.012	
UPSTREAM INVERT	84.94	FT	85.20	FT	85.30	FT
DOWNSTREAM INVERT	85.37	FT	85.10	FT	85.10	FT
CRITICAL ELEVATION	89.5	FT	93.00	FT	93.00	FT
<u>DETERMINE FLOWRATES (Q):</u>						
ASSUMED VELOCITY (25 YR)	6.00	FT/S	Headwater Elevation	Headwater Elevation	Headwater Elevation	Headwater Elevation
Q (25 YR) = V (25 YR) * TOTAL AREA	29	CFS	89.53	FT	88.70	FT
Q (50 YR) = 1.25 * Q (25 YR)	37	CFS	89.59	FT	89.13	FT
Q (100 YR) = 1.40 * Q (25 YR)	41	CFS	89.60	FT	89.40	FT
Q (500 YR) = 1.70 * Q (100 YR)	70	CFS		FT		FT

NOTES:

Survey Adjacent Wetlands, SHWT Avg **88.0** FT Tailwater used
Overtopping Post (77.7 cfs) **93.0** FT
Low Edge of Travel Lane (129+45) **91.8** FT 50YR DHW is lower

Analysis done with HY-8 Version 7.3 (Jan. 2013)

PROJECT: POINCIANA PARKWAY
SUBJECT: EXISTING / PROPOSED CULVERT ANALYSIS

CROSSDRAIN CHARACTERISTICS:

CROSS DRAIN NO. LOCATION	Existing		CD-4A Proposed		ULTIMATE	
	140+74		140+74		140+74	
WIDTH	0.00	FT	0.00	FT	0.00	FT
HEIGHT	0.00	FT	0.00	FT	0.00	FT
BARRELS	1		1		1	
DIAMETER	24.00	IN	24.00	IN	24.00	IN
LENGTH	88.00	FT	88.00	FT	156.00	FT
TOTAL CROSS-SECTIONAL AREA	3.14	SF	3.14	SF	3.14	SF
MANNING'S ROUGHNESS	0.012		0.012		0.012	
UPSTREAM INVERT	82.85	FT	82.80	FT	83.00	FT
DOWNSTREAM INVERT	82.42	FT	82.00	FT	82.00	FT
CRITICAL ELEVATION	84.20	FT	84.20	FT	84.20	FT
<u>DETERMINE FLOWRATES (Q):</u>						
ASSUMED VELOCITY (25 YR)	6.00	FT/S	Headwater Elevation	Headwater Elevation	Headwater Elevation	Headwater Elevation
Q (25 YR) = V (25 YR) * TOTAL AREA	19	CFS	84.34	FT	84.34	FT
Q (50 YR) = 1.25 * Q (25 YR)	24	CFS	84.37	FT	84.36	FT
Q (100 YR) = 1.40 * Q (25 YR)	26	CFS	84.38	FT	84.37	FT
Q (500 YR) = 1.70 * Q (100 YR)	45	CFS	84.45	FT	84.45	FT

NOTES:

Surveyed Outfall Overflow Elevation **82.5** FT Tailwater used
Existing Connection to Adjacent Wetlands **84.2** FT
Low Edge of Travel Lane (143+00) **89.0** FT 50YR DHW is lower

Analysis done with HY-8 Version 7.3 (Jan. 2013)

PROJECT: POINCIANA PARKWAY
SUBJECT: EXISTING / PROPOSED CULVERT ANALYSIS

CROSSDRAIN CHARACTERISTICS:

CROSS DRAIN NO. LOCATION	CD-5					
	Existing		Proposed		ULTIMATE	
	152+32		152+55		152+55	
WIDTH	0.00	FT	0.00	FT	0.00	FT
HEIGHT	0.00	FT	0.00	FT	0.00	FT
BARRELS	1		2		2	
DIAMETER	24.00	IN	24.00	IN	24.00	IN
LENGTH	41.00	FT	81.00	FT	169.00	FT
TOTAL CROSS-SECTIONAL AREA	3.14	SF	6.28	SF	6.28	SF
MANNING'S ROUGHNESS	0.012		0.012		0.012	
UPSTREAM INVERT	81.79	FT	81.30	FT	81.40	FT
DOWNSTREAM INVERT	81.15	FT	81.20	FT	81.20	FT
CRITICAL ELEVATION *	84.27	FT	86.70	FT	86.70	FT
DETERMINE FLOWRATES (Q):						
ASSUMED VELOCITY (25 YR)	6.00	FT/S	Headwater Elevation	Headwater Elevation	Headwater Elevation	Headwater Elevation
Q (25 YR) = V (25 YR) * TOTAL AREA	19	CFS	84.30	FT	83.08	FT
Q (50 YR) = 1.25 * Q (25 YR)	24	CFS	84.33	FT	83.37	FT
Q (100 YR) = 1.40 * Q (25 YR)	26	CFS	84.34	FT	83.48	FT
Q (500 YR) = 1.70 * Q (100 YR)	45	CFS		FT		FT

NOTES:

- Survey Adjacent Wetlands, SHWT Avg **81.4** FT Tailwater used
- * TOP OF ROAD AT STATION 152+30, RT
Overtopping Post (61.9 cfs) **86.7** FT
- Low Edge of Travel Lane (152+55) **85.3** FT 50YR DHW is lower

Analysis done with HY-8 Version 7.3 (Jan. 2013)

PROJECT: POINCIANA PARKWAY
SUBJECT: EXISTING / PROPOSED CULVERT ANALYSIS

CROSSDRAIN CHARACTERISTICS:

CROSS DRAIN NO. LOCATION	Existing		CD-6 Proposed		ULTIMATE	
	173+60		174+64		174+64	
WIDTH	0.00	FT	38.00	IN	38.00	FT
HEIGHT	0.00	FT	24.00	IN	24.00	FT
BARRELS	1		2		2	
DIAMETER	24.00	IN	0.00	IN	0.00	IN
LENGTH	20.00	FT	103.00	FT	170.00	FT
TOTAL CROSS-SECTIONAL AREA	3.14	SF	9.95	SF	9.95	SF
MANNING'S ROUGHNESS	0.024		0.012		0.012	
UPSTREAM INVERT	75.25	FT	74.64	FT	74.80	FT
DOWNSTREAM INVERT	74.89	FT	74.40	FT	74.40	FT
CRITICAL ELEVATION *	77.52	FT	80.70	FT	80.70	FT
DETERMINE FLOWRATES (Q):						
ASSUMED VELOCITY (25 YR)	6.00	FT/S	Headwater Elevation	Headwater Elevation	Headwater Elevation	Headwater Elevation
Q (25 YR) = V (25 YR) * TOTAL AREA	19	CFS	77.57	FT	77.12	FT
Q (50 YR) = 1.25 * Q (25 YR)	24	CFS	77.58	FT	77.20	FT
Q (100 YR) = 1.40 * Q (25 YR)	26	CFS	77.59	FT	77.23	FT
Q (500 YR) = 1.70 * Q (100 YR)	45	CFS	77.64	FT	77.69	FT

NOTES

- a) Crown of Existing Pipe **76.89** FT
- b) Wetland Elevation Downstream (ACOE) **77.00** FT Tailwater used
- c) Top of Existing Road at Station 173+60 **77.52** FT
- d) Top of Proposed Road at Station 175+00 **80.70** FT
- e) Low Edge of Travel Lane (175+80) **79.96** FT 50YR DHW is lower

Analysis done with HY-8 Version 7.3 (Jan. 2013)

FDOT Straight Line Diagrams

	INSIDE URBAN, OUTSIDE CITY * FOUR CORNERS * S ORANGE BLOSSOM TRL * SR 600 * US 17/US 92 POLK CO LINE 0.000 0.005 0.009 0.009 0.000 56.0' - 24.0' 2 - 12.0' RDWY 2 - 4.0' PVD SHLD1 2 - 12.0' LWN SHLD2 28/FC-0 0.094 28/FC-9.5 CURVE DATA NOT FIELD VERIFIED #0001 26.4' BR 0.353 0.358 0.000 URBAN PRIN ART OTHER 55MPH ACCESS CLASS03 NHS/MAP-21 PRINCIPAL ARTERIALS											INSIDE URBAN, OUTSIDE CITY * KISSIMMEE * S ORANGE BLOSSOM TRL * SR 600 * US 17/US 92 1.915 1.915 53.0' - 26.0' 2 - 13.0' RDWY 4.0' PVD SHLD1 - LT 10.0' PVD SHLD1 - RT 10.0' LWN SHLD2 - LT 3.0' VG SHLD2 - RT 1.915 2.018 28/FC-9.5 28/FC-9.5 B=S76°12'00"E 1.915 URBAN PRIN ART OTHER 55MPH ACCESS CLASS03 NHS/MAP-21 PRINCIPAL ARTERIALS
ROADWAY FEATURES												
LANE WIDTHS ARE AVERAGED												
ROADWAY COMPOSITION												
HORIZONTAL ALIGNMENT												
STRUCTURE DESCRIPTION												
SIS												
FUN CLASS												
SPEED LIMIT												
AC MAN CLS												
NHS												

	SUWANNE AVE 3.055 IMMOKALEE ST 3.091 TALLAHASSEE BLVD 3.157 MANATEE ST 3.225 HOPE ST 3.284 CHARITY ST 3.284 SHEPHERD LN 3.341 NOCATEE ST 3.341 AVE A 4.117 4.190 622952-B AVE B 4.278 POINCIANA BLVD 4.572 LOUIS DR 4.934 PINE LAKE TR PK 5.149 DOLORES DR 5.334 WHISPERING PINES BLV 5.546 ALEXANDER ST 5.546											
ROADWAY FEATURES												
LANE WIDTHS ARE AVERAGED												
ROADWAY COMPOSITION												
HORIZONTAL ALIGNMENT												
STRUCTURE DESCRIPTION												
SIS												
FUN CLASS												
SPEED LIMIT												
AC MAN CLS												
NHS												

5 YR INV	SLD REV	BMP	EMP	INV	SLD REV	SECTION STATUS	INT. or US ROUTE NO.	STATE ROAD NO.	COUNTY	DISTRICT	ROADWAY ID	SHEET NO:
DATE	09/06/2012	09/07/2012	000.000	010.750	12/18/2014 FC	12/18/2014 FC	02	US 17/US 92	SR 600	POLK	16050000	2 OF 2
BY	DEC	DEC	000.000	001.175	03/21/2014 DEC	04/08/2014 DEC						

FLORIDA DEPARTMENT OF TRANSPORTATION
STRAIGHT LINE DIAGRAM OF ROAD INVENTORY

ROADWAY FEATURES	<p>OUTSIDE CITY & URBAN</p> <ul style="list-style-type: none"> *K=US-17/92 *SR 600 *US 17/US 92 <p>LANE WIDTHS ARE AVERAGED</p> <p>48.0' - 24.0' 2 - 12.0' RDWY 2 - 5.0' PVD SHLD1 2 - 7.0' LWN SHLD2</p>
ROADWAY COMPOSITION	28/FC-2
HORIZONTAL ALIGNMENT	CURVE DATA NOT FIELD VERIFIED
STRUCTURE DESCRIPTION	<p>B=N29°19'00"E</p> <p>6.714 1-2' X 2' X 75' CBC</p> <p>6.975 1-2' X 2' X 70' CBC</p> <p>7.297 1-30" X 72' CC</p> <p>7.450 1-30" X 76' CC</p> <p>7.624 KISSIMMEE SOUTH ENT</p> <p>7.615 SUNNY ACRES RD</p> <p>7.624 HERBS LOST CREEK</p> <p>7.878 DEER RUN DR</p> <p>7.963 ORANGE COSMOS BLVD</p> <p>8.088 LOUGHMANS CREEK</p> <p>8.188 PROVIDENCE BLVD</p> <p>8.828</p> <p>7.878 60.0' - 24.0' 2 - 12.0' RDWY 12.0 PVD MED 2 - 5.0' PVD SHLD1 2 - 7.0' LWN SHLD2</p> <p>8.188 #0120 21' CB</p> <p>8.192</p> <p>8.916 1-24" X 84' CC</p>
DISTRICT USE	
SIS	
FUN CLASS	RURAL PRIN ART OTHER

ROADWAY FEATURES	<p>INSIDE URBAN, OUTSIDE CITY * FOUR CORNERS</p> <p>US 17/92 > SR 600 ></p> <p>OSCEOLA CO LINE</p> <p>SECTION ENDS @ OSCEOLA CO LINE MP: 10.750</p> <p>END MP: 10.750 NET ROADWAY ID LENGTH: 10.750</p> <p>GPS COORDINATES 28° 14' 56.006" N 81° 33' 05.2532" W</p>
ROADWAY COMPOSITION	28/FC-2
HORIZONTAL ALIGNMENT	CURVE DATA NOT FIELD VERIFIED
STRUCTURE DESCRIPTION	<p>B=N29°19'00"E</p> <p>9.037 48.0' - 24.0' 2 - 12.0' RDWY 2 - 5.0' PVD SHLD1 2 - 7.0' LWN SHLD2</p> <p>9.219 62.0' - 24.0' 2 - 12.0' RDWY 12.0 PVD MED 5.0' PVD SHLD1 - LT 4.0' PVD SHLD1 - RT 8.0' LWN SHLD2 - LT 9.0' LWN SHLD2 - RT</p> <p>9.592 40.0' - 24.0' 2 - 12.0' RDWY 12.0 PVD MED 2 - 2.0' C&G SHLD1</p> <p>10.036 48.0' - 24.0' 2 - 12.0' RDWY 2 - 5.0' PVD SHLD1 2 - 7.0' LWN SHLD2</p> <p>9.410 HART RD</p> <p>9.758 GAINES RD</p> <p>9.806 RONALD REAGAN RD</p> <p>9.806 KINNY HARMON RD</p> <p>10.321 PARKER RD</p> <p>10.546</p> <p>9.605 1-6' X 3' X 66' CBC</p> <p>10.354 1-4' X 3' X 65' CBC</p> <p>10.661 1-10' X 3' X 75' CBC</p> <p>PC=10.300 PI=10.511 PT=10.722 Δ=4°28'00.00" D=0°12'00.00"</p> <p>B=N33°47'00"E</p>
DISTRICT USE	
SIS	
FUN CLASS	RURAL PRIN ART OTHER

Appendix C

Field Review Notes

Date: March 18, 2019

Time: 8:30am

Project Number: 599-224

Weather Conditions: Cloudy, cool

Distribution

Name	Organization
Makeese Powe, E.I.	The Balmoral Group
Lori Stanfill, P.E.	The Balmoral Group

Review of Work

Review and verification of pipe sizes and conditions within project area.

Comments

Item	Description
Resident Comment	[Just South of US-92 and Labor Camp Road] Concerned resident, Everette Davis, says pipe has not been attended to since the last hurricane. There is a tree that was uprooted out the ground and now within the flow's path. Pictures were taken. Resident says he had to get his son to help him saw the tree down to a point of non-obstruction. He would love to chat with someone from the city to resolve this. (321)-443-4192
Resident Comment	[Old Kissimmee Road and Parker Road] Concerned Polk county resident says pipe has not been cleaned out in nearly 15 years.
Erosion	[Just East of Delmar Lane and Kinney Harmon Road] East end of Northern headwall.

Field notes may be found in:


Poinciana Parkway Location Hydraulics Report - Appendix C

Photos

Photos taken during field visit can be found in:

Poinciana Parkway Location Hydraulics Report - Appendix C

Plugged - not fully \approx 18" metal pipe



Legend

- ▲ Field Recon. (Low Priority)
- ▲ Field Recon.
- ➔ Proposed Cross Drains
- ▬ Existing Cross Drains
- Basins_Alt5
- Basins_Alt1A
- Basins_Alt4A



165 Lincoln Avenue
Winter Park, Florida 32789

FIELD SHEETS
03/18/2019



POINCIANA PARKWAY EXTENSION

CFX PD&E Study
ORANGE & OSCEOLA COUNTY, FLORIDA



Legend

- ▲ Field Recon.
- ▬ Existing Cross Drains

Double 24" Verify size and condition; Need photo

Double 24" x 38" Verify size and condition; Need photo

≈ 30" metal pipe ⇒ U.S. pipe
POINCIANA PARKWAY EXTENSION

CFX PD&E Study
 ORANGE & OSCEOLA COUNTY, FLORIDA



165 Lincoln Avenue
 Winter Park, Florida 32789

FIELD SHEETS
 03/18/2019





Legend

- ▲ Field Recon.
- ▬ Existing Cross Drains

Verify size and condition; Need photo

Double 24"

-verified

CD-1-04

CD-1-05

Panopaker Ln

Kinney Harmon Rd

Kinney Harmon Rd



165 Lincoln Avenue
Winter Park, Florida 32789

FIELD SHEETS
03/18/2019



POINCIANA PARKWAY EXTENSION

CFX PD&E Study
ORANGE & OSCEOLA COUNTY, FLORIDA



Legend

- ▲ Field Recon.
- ▬ Existing Cross Drains

Verify size and condition; Need photo
- verified 36"

6'x3' *OSB*
 Verify size and condition; Need photo



165 Lincoln Avenue
 Winter Park, Florida 32789

FIELD SHEETS
 03/18/2019



POINCIANA PARKWAY EXTENSION

CFX PD&E Study
 ORANGE & OSCEOLA COUNTY, FLORIDA



Legend


- ▲ Field Recon.
- ▶ Existing Cross Drains

Verify size and condition; Need photo




The Balmoral Group
 165 Lincoln Avenue
 Winter Park, Florida 32789

FIELD SHEETS
 03/18/2019



0 0.02 0.04 0.08
 Miles

POINCIANA PARKWAY EXTENSION
 CFX PD&E Study
 ORANGE & OSCEOLA COUNTY, FLORIDA



Legend

- ▲ Field Recon.
- ▶ Existing Cross Drains

unknown
Need size; Need photo; verify condition

Verify size and condition; Need photo

Verify if there's anything here

① 5.5'(W) x 5.0'(H) (approx due to silt & vegetation)
FIELD SHEETS
03/18/2019



POINCIANA PARKWAY EXTENSION

CFX PD&E Study
ORANGE & OSCEOLA COUNTY, FLORIDA

The Balmoral Group
165 Lincoln Avenue
Winter Park, Florida 32789



Concerned resident, Everette Davis, says pipe has not been attended to since the last hurricane. There is a tree that was uprooted out the ground and now within the flow's path. Pictures were taken. Resident says he had to get his son to help him saw the tree down to a point of non-obstruction. He would love to chat with someone from the city to resolve this.

Legend

- ▲ Field Recon. (Low Priority)
- ▲ Field Recon.
- Existing Cross Drains



165 Lincoln Avenue
Winter Park, Florida 32789

FIELD SHEETS
03/18/2019




POINCIANA PARKWAY EXTENSION

CFX PD&E Study
ORANGE & OSCEOLA COUNTY, FLORIDA

→ Everette Davis & Willie Davis 321-443-4192

2-DO1
could not
verify
2-604



Legend

- ▲ Field Recon.
- ▬ Existing Cross Drains

Verify size and condition; Need photo

Unknown size; Need photo; verify condition

Verify if there's anything here

has not
been cleaned out
in 15 yrs
concerned
resident



165 Lincoln Avenue
Winter Park, Florida 32789

FIELD SHEETS
03/18/2019



POINCIANA PARKWAY EXTENSION

CFX PD&E Study
ORANGE & OSCEOLA COUNTY, FLORIDA

Could not
find in
field



Legend

- ▲ Field Recon.
- ➡ Existing Cross Drains

old brick road
60MP

Verify if there's anything here

Triple 5'x8' CBC
Twilight
Verify size and condition; Need photo

26.4-ft Bridge over Reedy-Creek
Verify condition; Any scour? Need photo

Moya n Camps - good hair cond.



165 Lincoln Avenue
Winter Park, Florida 32789

Bad Pavement - water may d.t. road here

FIELD SHEETS
03/18/2019




3 @ 8'x4' Bridge

no apparent scour/erosion - silted - not minor or major
Culvert → good condition

POINCIANA PARKWAY EXTENSION

CFX PD&E Study
ORANGE & OSCEOLA COUNTY, FLORIDA



Legend

- ▲ Field Recon.
- ▬ Existing Cross Drains

30"
 Six 29" x 45"
 Verify size and condition; Need photo

Wien → outfall to West
 FIELD SHEETS
 03/18/2019
 heavy vegetation
 1/2" minor silt



POINCIANA PARKWAY EXTENSION

CFX PD&E Study
 ORANGE & OSCEOLA COUNTY, FLORIDA

165 Lincoln Avenue
 Winter Park, Florida 32789



Legend

- ▲ Field Recon.
- ▬ Existing Cross Drains

Osceola Polk Line Rd

Verify size and condition; Need photo

Osceola Polk Line Rd

unknown

24" RCP - 1/2 silted

unknown

5mm pipe & 24" picture

- no measure
- me up



165 Lincoln Avenue
Winter Park, Florida 32789

FIELD SHEETS
03/18/2019



POINCIANA PARKWAY EXTENSION

CFX PD&E Study
ORANGE & OSCEOLA COUNTY, FLORIDA



EX-CD-1; Upstream End (Northwest), Facing North



EX-CD-1; Upstream End (Northwest), Facing Southeast



EX-CD-1; Upstream End (Northwest), Facing Southeast



EX-CD-1; Upstream End (Northwest), Facing Southwest



EX-CD-4; Downstream End (Northeast), Facing Northeast



EX-CD-4; Upstream End (Southwest), Facing Northeast



EX-CD-4; Upstream End (Southwest), Facing Southwest



EX-CD-4A; Upstream End (Southwest), Facing Northeast



EX-CD-4A; Upstream End (Southwest), Facing Northeast



EX-CD-4A; Upstream End (Southwest), Facing Southwest



EX-CD-5; Downstream End (Northeast), Facing East



EX-CD-5; Upstream End (Southwest), Facing East



EX-CD-5; Upstream End (Southwest), Facing Northeast



EX-CD-6; Downstream End (Northeast)



EX-CD-6; Downstream End (Northeast), Facing Southeast



EX-CD-6; Upstream End (Southwest)



EX-CD-6; Upstream End (Southwest), Facing Northeast




EX-CD-6; Downstream End (Northeast), Facing Northwest



EX-A; Downstream End (East)



EX-A; Downstream End (East), Facing North



EX-A; Downstream End (East), Facing North



EX-A; Upstream End (West)



EX-A; Downstream End (East), Facing South



EX-A; Upstream End (West)



EX-A; Upstream End (West)



EX-B; Downstream End (South)



EX-B; Downstream End (South), Facing West



EX-B; Downstream End (South)



EX-C; Upstream End (Northwest)



EX-C; Upstream End (Northwest), Facing North



EX-C; Downstream End (Southeast)



EX-C; Downstream End (Southeast), Facing Northwest



EX-C; Downstream End (Southeast), Facing Northwest



EX-C; Downstream End (Southeast), Facing Northwest



EX-C; Downstream End (Southeast), Facing Northeast



EX-D; Upstream End (Northwest), Facing Northwest



EX-D; Downstream End (Southeast)



EX-D; Downstream End (Southeast), Facing Southeast



EX-D; Downstream End (Southeast), Facing Northwest



EX-D; Downstream End (Southeast)



EX-E; Upstream End (West), Facing East



EX-E; Upstream End (West), Facing East



EX-E; Upstream End (West), Facing South



EX-F; Upstream End (North), Facing North



EX-F; Upstream End (North), Facing North



EX-F; Downstream End (South), Facing North



EX-G; Upstream End (Southwest)



EX-G; Upstream End (Southwest), Facing Southwest



EX-L; Upstream End (Northwest), Facing East



EX-L; Downstream End (Southeast)



EX-N; Upstream End (Northwest), Facing Northwest



EX-N; Upstream (Northwest), Facing Southwest



EX-N; Downstream (Southeast), Facing Northwest



EX-N; Downstream (Southeast), Facing Northwest

Appendix D

Calculations

PROJECT: CFX Feasibility Study: I-4 / Poinciana Parkway Connector Extension
 LOCATION: Osceola and Polk County, Florida

PREPARED:
 CHECKED:

MDP DATE: 05/15/19
 JAN DATE: 05/15/19

Table B.1 - Existing Offsite Conveyance Summary

Existing Cross Drain ID	Proposed Cross Drain ID	Size	Source	Existing Length	Existing 50-Yr		Existing 100-Yr		Comment
				(LF)	Stage (ft NAVD)	Flow (cfs)	Stage (ft NAVD)	Flow (cfs)	
EX-A1	CD-1-01	6-29"x45" Pipes	Field Review 3/18/2019; SFWMD Permit Application 020702-14 & SFWMD Permit Application 43023879	52*	--	--	83.0	554.47	Existing information is from ICPR Routing; max stage in EAST5WET; Max Outflow from EAST5WET; Converted to NAVD (SFWMD ERP App. 43023879)
EX-A2	CD-4-01, CD-5-01	6-29"x45" Pipes	Field Review 3/18/2019; SFWMD Permit Application 020702-14 & SFWMD Permit Application 43023879	52*	--	--	78.8	584.05	Existing information is from ICPR Routing Upstream of Railroad; Max stage in EAST7WET; Max Outflow from EAST7WET; Converted to NAVD (SFWMD ERP App. 43023879)
EX-B	CD-1-02	2-60" Pipes (act as control structure with DBIs upstream)	Field Review 3/18/2019; SFWMD Permit Application 020702-14 & SFWMD Permit Application 43023879	72*	--	--	85.2	153.47	Existing information is from ICPR Routing, Upstream of Railroad, SOUTH5; Converted to NAVD (SFWMD ERP App. 43023879)
EX-CD-1	CD-1-03	6'x3' CBC	Referred to as CD-1 in docs; Field Review 3/18/2019; SFWMD Permit Application 141010-12	88*	94.3	135	94.6	151	Existing information is from HY-8 using 6 fps velocity method; Converted to NAVD (SFWMD ERP App. 141010-12)
EX-CD-4	CD-1-04, CD-1-05	2-24" Pipes	Referred to as CD-4 in docs; Field Review 3/18/2019; SFWMD Permit Application 141010-12	86*	88.2	37	88.5	41	Existing information is from HY-8 using 6 fps velocity method; Converted to NAVD (SFWMD ERP App. 141010-12)
EX-CD-4A	CD-1-06	24" Pipe	Referred to as CD-4A in docs; Field Review 3/18/2019; SFWMD Permit Application 141010-12	88*	83.4	24	83.4	26	Existing information is from HY-8 using 6 fps velocity method; Converted to NAVD (SFWMD ERP App. 141010-12)
EX-CD-5	CD-1-07, CD-4-05A, CD-4-05B, CD-5-05A, CD-5-05B	2-24" Pipes	Referred to as CD-5 in docs; Field Review 3/18/2019; SFWMD Permit Application 141010-12	81*	82.4	24	82.5	26	Existing information is from HY-8 using 6 fps velocity method; Converted to NAVD (SFWMD ERP App. 141010-12)
EX-CD-6	CD-1-08, CD-4-06, CD-5-06, CD-5B-05B	2-24"x38" Pipes	Referred to as CD-6 in docs; Field Review 3/18/2019; SFWMD Permit Application 141010-12	103*	76.3	24	76.3	26	Existing information is from HY-8 using 6 fps velocity method; Converted to NAVD (SFWMD ERP App. 141010-12)
EX-C	CD-4-02, CD-5-02	10'x3' CBC	Field Review 3/18/2019; US 17/US 92 FDOT Straight Line Diagram (Polk Co) [Road ID: 16050000]	72*	--	--	73.3	158.85	Existing information is from ICPR Routing, Node 17-92SE; Converted to NAVD (SFWMD ERP App. 43023879)
EX-D	CD-4-03, CD-5-03	3-8'x4' CBC (Bridge Culvert #920001)	Field Review 3/18/2019; US 17/US 92 FDOT Straight Line Diagram (Osceola Co)	91*	--	--	68.6	613.05	Existing information is from ICPR Routing, Node 17-92NE; Converted to NAVD (SFWMD ERP App. 43023879)

* Measured off Aerial Imagery

Table B.2 - Proposed Offsite Conveyance Summary

Cross Drain ID	Required Minimum Size	Design Flow (cfs)	Basin Area (ac)	Method	Notes
CD-1-01	9-38"x60" Pipes	554.47	--	Existing Information	Flow from Old Kissimmee Road Basin Flood Study, Node EAST5WET (SWFWMD ERP App. 43023879) TW from FEMA BFE, Inverts from DEM
CD-1-02	4-60" Pipes	153.47	--	Existing Information	Flow from Old Kissimmee Road Basin Flood Study, Link RRSOUTH (SWFWMD ERP App. 43023879) TW from FEMA BFE, Inverts from DEM
CD-1-03	6'x3' CBC	124.79	39.60	Rational Method + Contributing Flow	Contributing Flow from Pond 800 (SWFWMD ERP App. 43028086)
CD-1-04	5-48" Pipes	12.00	119.27	Rational Method + Contributing Flow	Contributing flow from CD-1-03 and Providence Development
CD-1-05	3-36" Pipes	44.92	13.83	Rational Method + Contributing Flow	Contributing flow from Providence Development
CD-1-06	2-36" Pipes	26.67	8.90	Rational Method	N/A
CD-1-07	5-36" Pipes	264.98	95.64	Rational Method + Contributing Flow	Contributing flow from Providence Development
CD-1-08	2-38"x60" Pipes	106.69	59.90	Rational Method + Contributing Flow	Contributing flow from Nature's Preserve Development
CD-4-01	7-38"x60" Pipes	584.05	--	Existing Information	Flow from Old Kissimmee Road Basin Flood Study, Links at RRNORTH (SWFWMD ERP App. 43023879) TW from FEMA BFE, Inverts from DEM
CD-4-02	10'x3' CBC48" Pipe	158.85	--	Existing Information	Flow from Old Kissimmee Road Basin Flood Study, Node 17-92SE (SWFWMD ERP App. 43023879)
CD-4-03	3-8'x4' BRIDGE CULVERT	613.05	--	Existing Information	Flow from Old Kissimmee Road Basin Flood Study, Node 17-92NE Outflow (SWFWMD ERP App. 43023879) Inverts from DEM, TW at Crown of CBC
CD-4-04	BRIDGE	--	--	N/A	N/A
CD-4-05A	6-36" Pipes	276.49	107.62	Rational Method + Contributing Flow	Contributing flow from Providence Development
CD-4-05B	6-36" Pipes	302.16	10.85	Rational Method + Contributing Flow	Contributing flow from CD-4-05A
CD-4-06	2-38"x60" Pipes	109.72	63.25	Rational Method + Contributing Flow	Contributing flow from Nature's Preserve Development
CD-5-01	7-38"x60" Pipes	584.05	--	Existing Information	Flow from Old Kissimmee Road Basin Flood Study, Links at RRNORTH (SWFWMD ERP App. 43023879) TW from FEMA BFE, Inverts from DEM
CD-5-02	10'x3' CBC48" Pipe	158.85	--	Existing Information	Flow from Old Kissimmee Road Basin Flood Study, Node 17-92SE (SWFWMD ERP App. 43023879)
CD-5-03	3-8'x4' BRIDGE CULVERT	613.05	--	Existing Information	Flow from Old Kissimmee Road Basin Flood Study, Node 17-92NE Outflow (SWFWMD ERP App. 43023879) Inverts from DEM, TW at Crown of CBC
CD-5-04	BRIDGE	--	--	N/A	N/A
CD-5-05A	4-36" Pipes	276.39	106.40	Rational Method + Contributing Flow	Contributing flow from Providence Development
CD-5-05B	6-36" Pipes	355.42	41.34	Rational Method + Contributing Flow	Contributing flow from CD-5-05A
CD-5-06	2-38"x60" Pipes	110.32	64.02	Rational Method + Contributing Flow	Contributing flow from Nature's Preserve Development
CD-5B-05B	2-38"x60" Pipes	134.26	86.96	Rational Method + Contributing Flow	Contributing flow from Nature's Preserve Development

* Proposed pipe size from cross drain analysis

PROJECT: Poinciana Parkway Connector PD&E
 LOCATION: Osceola and Polk County, Florida

PREPARED: MDP DATE: 05/15/19
 CHECKED: JAN DATE: 05/15/19

Table B.3 - Cross-Drain DHW Summary

Proposed Cross Drain ID	Existing Cross Drain				Proposed Cross Drain			Difference in Proposed DHW - Reference* (ft)	Comments
	Existing Cross Drain ID	Size	Reference		Size	DHW			
			CD DHW	Min. Rdwy Elev.		50 YEAR	100 YEAR		
CD-1-01	EX-A1	6-29"x45" Pipes	83.0 +	85.3	9-38"x60" Pipes	--	83.11	-2.2	(Min. Rdwy Elev. from Pond J in Sandy Ridge Development)
CD-1-02	EX-B	2-60" Pipes (act as control structure with DBIs upstream)	85.2 +	85.3	4-60" Pipes	--	85.15	-0.2	(Min. Rdwy Elev. from Pond J in Sandy Ridge Development)
CD-1-03	EX-CD-1	6'x3' CBC	94.3	96.0	6'x3' CBC	94.08	94.55	-1.9	(Min. Rdwy Elev. from CD-1 Low Edge of Travel Lane in SWFWMD ERP App. 141010-12)
CD-1-04	EX-CD-4	2-24" Pipes	88.2	96.4	5-48" Pipes	91.09	91.35	-5.3	Remains in wetland (Min. Rdwy Elev. from Pond 11 in Providence N2-3 Subdivision)
CD-1-05	EX-CD-4	2-24" Pipes	88.2	97.8	3-36" Pipes	89.79	89.93	-8.0	(Min. Rdwy Elev. from Pond 9 in Providence N2-3 Subdivision)
CD-1-06	EX-CD-4A	24" Pipe	83.4	88.7	2-36" Pipes	87.2	87.48	-1.5	Remains in wetland (Min. Rdwy Elev. from Pond 2 in Providence N26 Subdivision)
CD-1-07	EX-CD-5	2-24" Pipes	82.4	92.1	5-36" Pipes	86.36	87.24	-5.8	Remains in wetland (Min. Rdwy Elev. from Pond RD-38 in Providence N26 Subdivision)
CD-1-08	EX-CD-6	2-24"x38" Pipes	76.3	82.9	2-38"x60" Pipes	76.98	77.22	-5.9	(Min. Rdwy Elev. from Pond 28.3 in Nature's Preserve Development)
CD-4-01	EX-A2	6-29"x45" Pipes	78.8 +	85.3	7-38"x60" Pipes	--	81.3	-4.0	Remains in wetlands & channel (Min. Rdwy Elev. from Pond J in Sandy Ridge Development)
CD-4-02	EX-C	10'x3' CBC	73.3 +	--	10'x3' CBC 48" Pipe	--	73.74	0.5	Flooding issues at this pipe location
CD-4-03	EX-D	3-8'x4' CBC (Bridge Culvert #920001)	68.6 +	--	3-8'x4' CBC (Bridge Culvert #920001)	--	68.71	0.1	
CD-4-04	--	--	--	--	3,267-ft of New Bridge	--	--	N/A	
CD-4-05A	EX-CD-5	2-24" Pipes	82.4	92.1	6-36" Pipes	86.06	86.86	-6.1	Does not incroach on adjacent property (Min. Rdwy Elev. from Pond RD-38 in Providence N26 Subdivision)
CD-4-05B	EX-CD-5	2-24" Pipes	82.4	92.1	6-36" Pipes	84.04	84.78	-8.1	Does not incroach on adjacent property (Min. Rdwy Elev. from Pond RD-38 in Providence N26 Subdivision)
CD-4-06	EX-CD-6	2-24"x38" Pipes	76.3	82.9	2-38"x60" Pipes	77.08	77.32	-5.8	Does not incroach on adjacent property (Min. Rdwy Elev. from Pond 28.3 in Nature's Preserve Development)
CD-5-01	EX-A2	6-29"x45" Pipes	78.8 +	85.3	7-38"x60" Pipes	--	81.3	-4.0	Remains in wetlands & channel (Min. Rdwy Elev. from Pond J in Sandy Ridge Development)
CD-5-02	EX-C	10'x3' CBC	73.3 +	--	10'x3' CBC 48" Pipe	--	73.74	0.5	Flooding issues at this pipe location
CD-5-03	EX-D	3-8'x4' CBC (Bridge Culvert #920001)	68.6 +	--	3-8'x4' CBC (Bridge Culvert #920001)	--	68.71	0.1	
CD-5-04	--	--	--	--	3,272-ft of New Bridge	--	--	N/A	
CD-5-05A	EX-CD-5	2-24" Pipes	82.5	92.1	4-36" Pipes	86.75	87.66	-5.4	Does not incroach on adjacent property (Min. Rdwy Elev. from Pond RD-38 in Providence N26 Subdivision)
CD-5-05B	EX-CD-5	2-24" Pipes	82.5	92.1	6-36" Pipes	85.54	86.51	-6.6	Does not incroach on adjacent property (Min. Rdwy Elev. from Pond RD-38 in Providence N26 Subdivision)
CD-5-06	EX-CD-6	2-24"x38" Pipes	76.3	82.9	2-38"x60" Pipes	77.58	77.58	-5.3	Does not incroach on adjacent property (Min. Rdwy Elev. from Pond 28.3 in Nature's Preserve Development)
CD-5B-05B	EX-CD-6	2-24"x38" Pipes	76.3	82.9	2-38"x60" Pipes	77.33	77.55	-5.5	(Min. Rdwy Elev. from Pond 28.3 in Nature's Preserve Development)

DHW = Design High Water Elevation [ft]

+ 100 Year DHW retrieved from ERP

* Minimum Roadway Elevation used as reference where present on table

PROJECT: CFX Feasibility Study: / Poinciana Parkway Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: JAN

DATE: 05/15/19
DATE: 05/15/19

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-1-01
------------------	---------

Total Contributing Flow Calculations

Existing Flow from EAST5WET =	554.47	(Node EAST5WET, 100-yr Storm)
Existing Flow at Railroad =	584.05	(Links RRNORTH1 & RRNORTH2, 100-yr Storm)

(Contributing link flow attained from SWFWMD ERP App. 43023879)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	82.00	FEMA BFE
Roadway Crest Elevation	87.00	Assumed 5-ft above crown
Upstream Culvert Invert	78.0	From DEM
Downstream Culvert Invert	77.82	Minimum slope
Culvert length	358.0	Measured from GIS, assume full R/W width
Upstream Est. SHWL Elev (ft-NAVD88)	79.0	NRCS Imagery estimate

Existing Permitted Culvert Conveyance Size	6 - 29 inch x 45 inch	In series upstream
--	-----------------------	--------------------

(Size information retrieved from SWFWMD Permit Application 43023879)

Proposed Culvert Size	9 - 38 inch x 60 inch
-----------------------	-----------------------

(Size retrieved from HY-8 version 7.50)

PROJECT: CFX Feasibility Study: / Poinciana Parkway Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: JAN

DATE: 05/15/19
DATE: 05/15/19

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-1-02
------------------	---------

Total Contributing Flow Calculations

Existing Flow at Railroad =	153.47	(Link RRSOUTH, 100-yr Storm)
-----------------------------	--------	------------------------------

(Contributing link flow attained from SWFWMD ERP App. 43023879)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	85.00	FEMA BFE
Roadway Crest Elevation	90.00	Assumed 5-ft above crown
Upstream Culvert Invert	80.0	Assumed invert for crown of pipe at tailwater
Downstream Culvert Invert	79.82	Minimum slope
Culvert length	358.0	Measured from GIS, assume full R/W width
Upstream Est. SHWL Elev (ft-NAVD88)	83.0	NRCS Imagery estimate

Existing Permitted Culvert Conveyance Size	2 - 60 inch	In series upstream
--	-------------	--------------------

(Size information retrieved from SWFWMD Permit Application 43023879)

Proposed Culvert Size	4-60 inch
-----------------------	-----------

(Size retrieved from HY-8 version 7.50)

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-1-03
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	30.1

Basin Runoff Calculations

Total Contributing Area (acres)	39.60
Pervious Contributing Area (acres)	39.20
Impervious Contributing Area (acres)	0.40
Weighted Runoff Coefficient ¹	0.37
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations


Event ²	25-year	Design	Base	Greatest
		50-year	100-year	500-yr
Intensity (in/hr) ³	5.59	6.13	6.70	N/A
Peak Flow (cfs)	74.60	89.25	101.65	146.64

Solve for 500-year flow rate using log-log graph based on the above 25, 50, and 100-year peak flow rates

$$y = Ax^{-B}$$

A= 36.675
 B= 0.223
 y= **146.64 cfs**
 x= 0.002


$$x = \sqrt[B]{\frac{A}{y}}$$



Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates shown below.

$$x = \sqrt[B]{\frac{A}{y}}$$

A= 64.529
 B= 0.166
 y= 227.58 cfs
 x= **0.05%**



Total Contributing Flow Calculations

Exist. Flow from Pond 800 =	35.54
Total Design Peak Flow (cfs)	124.79
Total Base Peak Flow (cfs)	137.19
Total Greatest Peak Flow (cfs)	182.18
Overtopping Flow - From HY8 (cfs)	227.58

SWFWMD ERP App. 43028086 (25-yr/24-hr Storm)

Lake Locke considered as a Closed Basin (SWFWMD ERP App. 43028086)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	90.97
Roadway Crest Elevation	98.10
Upstream Culvert Invert	90.1
Downstream Culvert Invert	89.82
Culvert length	222.0
Upstream Est. SHWL Elev (ft-NAVD88)	89.1

CBC Stainline used in ERP 141010-12 (Higher than FEMA BFE, 90.4)
 Assumed 5-ft above crown
 (Invert from SFWMD ERP 141010-12, Converted to NAVD)
 (CBC slope from SFWMD ERP 141010-12)
 Measured from GIS, extended 134 ft beyond the proposed EOS
 (Attained from SFWMD Permit Application 071212-21)

Existing Permitted Culvert Conveyance Size **6 feet x 3 feet**

(Size information retrieved from SWFWMD Permit Application 141010-12)

Proposed Culvert Size **6 feet x 3 feet**

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

PROJECT: CFX Feasibility Study / Poinciana Parkway Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: JAN

DATE: 05/15/19
DATE: 05/15/19

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-1-04
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	93.1

Basin Runoff Calculations

Total Contributing Area (acres)	119.27
Pervious Contributing Area (acres)	119.27
Impervious Contributing Area (acres)	0.00
Weighted Runoff Coefficient ¹	0.36
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations

Event ²	25-year	Design 50-year	Base 100-year	Greatest 500-yr
Intensity (in/hr) ³	2.88	3.20	3.40	N/A
Peak Flow (cfs)	113.32	137.50	152.07	217.04


(Used 500-year Log-Log graph to obtain basin runoff flow rate)

Solve for 500-year flow rate using log-log graph based on the above 25, 50, and 100-year peak flow rates

$$y = Ax^{-B}$$

A = 58.125
 B = 0.212
 y = **217.04 cfs**
 x = 0.002


$$x = \sqrt[B]{\frac{A}{y}}$$



Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates shown below.

$$x = \sqrt[B]{\frac{A}{y}}$$

A = 250.91
 B = 0.126
 y = 739.88 cfs
 x = **0.02%**



Total Contributing Flow Calculations

Design Flow from CD-1-03 (cfs)	124.79	(50-yr Storm)
Base Flow from CD-1-03 (cfs)	137.19	
Greatest Flow from CD-1-03 (cfs)	182.18	
Flow from Providence Development (cfs)	153.07	(25-yr/24-hr Storm)
Total Design Peak Flow (cfs)	415.35	
Total Base Peak Flow (cfs)	442.33	
Total Greatest Peak Flow (cfs)	552.29	

POND RD-1 = 4.416 (cfs)
 POND PN23-2 = 44.481 (cfs)
 POND PN23-5 = 49.113 (cfs)
 POND PN23-6 = 16.158 (cfs)
 POND PN23-11 = 9.476 (cfs)
 POND PN27 = 29.427 (cfs)
TOTAL = 153.07 (cfs)

(Contributing pond flows attained from SFWMD Permit Application 040220-40)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	87.07
Roadway Crest Elevation	95.50
Upstream Culvert Invert	86.5
Downstream Culvert Invert	86.00
Culvert length	342.0
Upstream Est. SHWL Elev (ft-NAVD88)	89.1

(Tailwater from HY-8 Input in SFWMD ERP 141010-12, Converted to NAVD)
 Assumed 5-ft above crown
 From DEM
 Assumed slope
 Measured from GIS, assume full R/W width
 (Attained from SFWMD Permit Application 071212-21)

Existing Permitted Culvert Conveyance Size 2 - 24 inch

(Size information retrieved from SFWMD Permit Application 141010-12)

Proposed Culvert Size 5- 48 inch

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-1-05
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	18.7

Basin Runoff Calculations

Total Contributing Area (acres)	13.83
Pervious Contributing Area (acres)	12.45
Impervious Contributing Area (acres)	1.38
Weighted Runoff Coefficient ¹	0.44
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations

Event ²	25-year	Design	Base	Greatest
		50-year	100-year	500-yr
Intensity (in/hr) ³	6.79	7.42	8.00	N/A
Peak Flow (cfs)	37.71	44.92	50.48	71.34

(Used 500-year Log-Log graph to obtain basin runoff flow rate)

Solve for 500-year flow rate using log-log graph on the above 25, 50, and 100-year peak flow rates

$$y = Ax^{-B}$$

A = 19.344
 B = 0.21
 y = **71.34 cfs**
 x = 0.002

$$x = \sqrt[B]{\frac{A}{y}}$$

Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates shown below.

$$x = \sqrt[B]{\frac{A}{y}}$$

A = 74.827
 B = 0.096
 y = 221.92
 x = 0.00%


Total Contributing Flow Calculations

Flow from Providence Development (cfs)	64.58
Total Design Peak Flow (cfs)	109.50
Total Base Peak Flow (cfs)	115.06
Total Greatest Peak Flow (cfs)	135.92

(25-yr/24-hr Storm)

POND PN23-9 = 64.579 (cfs)
TOTAL = 64.579 (cfs)

(Contributing pond flow attained from SFWMD Permit Application 040220-40)



Cross Drain Sizing Calculations

Tailwater Elevation/Source	87.07
Roadway Crest Elevation	94.50
Upstream Culvert Invert	86.5
Downstream Culvert Invert	86.00
Culvert length	343.0
Upstream Est. SHWL Elev (ft-NAVD88)	88.0

(Tailwater from HY-8 Input in SFWMD ERP 141010-12, Converted to NAVD)
 Assumed 5-ft above crown
 From DEM
 Assumed slope
 Measured from GIS, assume full R/W width
 (Attained from SFWMD Permit Application 071212-21)

Existing Permitted Culvert Conveyance Size	2 - 24 inch
--	-------------

(Size information retrieved from SFWMD Permit Application 141010-12)

Proposed Culvert Size	3 - 36 inch
-----------------------	--------------------

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-1-06
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	23.2

Basin Runoff Calculations

Total Contributing Area (acres)	8.90
Pervious Contributing Area (acres)	8.01
Impervious Contributing Area (acres)	0.89
Weighted Runoff Coefficient ¹	0.44
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations


Event ²	25-year	Design	Base	Greatest
		50-year	100-year	500-yr
Intensity (in/hr) ³	6.25	6.84	7.50	N/A
Peak Flow (cfs)	22.35	26.67	30.45	43.89

(Used 500-year Log-Log graph to obtain basin runoff flow rate)

Solve for 500-year flow rate using log-log graph on the above 25, 50, and 100-year peak flow rates

$$y = Ax^{-B}$$


A = 10.977
 B = 0.223
 y = **43.89 cfs**
 $x = \sqrt[B]{\frac{A}{y}}$
 x = 0.002



Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates. shown below.

$$x = \sqrt[B]{\frac{A}{y}}$$

A = 89.587
 B = 0.062
 y = 126.7
 x = 0.37%



Total Contributing Flow Calculations

Flow from Providence Development (cfs)	87.91
Total Design Peak Flow (cfs)	114.59
Total Base Peak Flow (cfs)	118.37
Total Greatest Peak Flow (cfs)	131.80

(25-yr/24-hr Storm)

POND PN23-8 = 75.526 (cfs)
 POND RD-3B = 12.387 (cfs)
TOTAL = 87.913 (cfs)

(Contributing pond flow attained from SFWMD Permit Application 040220-40)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	81.57
Roadway Crest Elevation	88.07
Upstream Culvert Invert	81.0
Downstream Culvert Invert	80.83
Culvert length	336.0
Upstream Est. SHWL Elev (ft-NAVD88)	80.5

(Surveyed Outfall Overflow Elev., SFWMD ERP 141010-12)
 (Low Edge of Pavement, SFWMD ERP 141010-12)
 From DEM
 Minimum slope
 Measured from GIS, assume full R/W width
 (Attained from SFWMD Permit Application 141010-12)

Existing Permitted Culvert Conveyance Size	24 inch
--	---------

(Size information retrieved from SWFWMD Permit Application 141010-12)

Proposed Culvert Size	2 - 36 inch
-----------------------	--------------------

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-1-07
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	42.7

Basin Runoff Calculations

Total Contributing Area (acres)	95.64
Pervious Contributing Area (acres)	90.86
Impervious Contributing Area (acres)	4.78
Weighted Runoff Coefficient ¹	0.40
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations


Event ²	25-year	Design	Base	Greatest
		50-year	100-year	500-yr
Intensity (in/hr) ³	4.70	5.17	5.70	N/A
Peak Flow (cfs)	164.40	197.37	226.58	330.45

(Used 500-year Log-Log graph to obtain basin runoff flow rate)

Solve for 500-year flow rate using log-log graph on the above 25, 50, and 100-year peak flow rates


$$y = Ax^{-B}$$

A = 78.64
 B = 0.231
 y = 330.45 cfs
 $x = \sqrt[B]{\frac{A}{y}}$
 x = 0.002



Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates shown below.

A = 130.67
 B = 0.179
 y = 329.73
 x = 0.57%



Total Contributing Flow Calculations

Flow from Providence Development (cfs)	67.61
Total Design Peak Flow (cfs)	264.98
Total Base Peak Flow (cfs)	294.19
Total Greatest Peak Flow (cfs)	398.06

(25-yr/24-hr Storm)

- POND PN2-8 = 36.23 (cfs)
- POND RD-3B = 12.39 (cfs)
- POND RD-3A = 12.62 (cfs)
- POND 10A-1 = 6.37 (cfs)
- TOTAL = 67.61 (cfs)

(Contributing pond flows attained from SWFMD Permit Application 040220-40)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	80.47
Roadway Crest Elevation	88.37
Upstream Culvert Invert	80.37
Downstream Culvert Invert	80.27
Culvert length	392.0
Upstream Est. SHWL Elev (ft-NAVD88)	80.5

(Tailwater from SFWMD ERP 141010-12, Converted to NAVD)
 Assumed 5-ft above crown
 (Invert from SFWMD ERP 141010-12, Converted to NAVD)
 (Culvert slope from SFWMD ERP 141010-12)
 Measured from GIS, assume full R/W width
 (Attained from SFWMD Permit Application 141010-12)

Existing Permitted Culvert Conveyance Size	2 - 24 inch
--	-------------

(Size information retrieved from SWFWMD Permit Application 141010-12)

Proposed Culvert Size	5 - 36 inch
-----------------------	-------------

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

Table B.4 - Proposed Offsite Conveyance Calculations

Existing Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-1-08
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	70.0

Basin Runoff Calculations

Total Contributing Area (acres)	59.90
Pervious Contributing Area (acres)	59.90
Impervious Contributing Area (acres)	0.00
Weighted Runoff Coefficient ¹	0.36
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations

Event ²	25-year	Design 50-year	Base 100-year	Greatest 500-yr
Intensity (in/hr) ³	3.51	3.88	4.30	N/A
Peak Flow (cfs)	69.35	83.77	96.59	142.99

(Used 500-year Log-Log graph to obtain basin runoff flow rate)

Solve for 500-year flow rate using log-log graph on the above 25, 50, and 100-year peak flow rates

$$y = Ax^{-B}$$



A = 32.378
 B = 0.239
 y = **142.99 cfs**
 x = 0.002

$$x = \sqrt[B]{\frac{A}{y}}$$

Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates shown below.

$$x = \sqrt[B]{\frac{A}{y}}$$

A = 49.545
 B = 0.194
 y = 214.66
 x = 0.05%



Total Contributing Flow Calculations

Flow from Natures Preserve Development (cfs)	22.92
Total Design Peak Flow (cfs)	106.69
Total Base Peak Flow (cfs)	119.51
Total Greatest Peak Flow (cfs)	165.91

(25-yr/72-hr Storm)

POND 2 & 3 = 15.12 (cfs)

POND4 = 2.60 (cfs)

POND5 = 5.20 (cfs)

TOTAL = 22.92 (cfs)

(Contributing pond flows attained from SFWMD Permit Application 101022-10)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	76.07
Roadway Crest Elevation	79.77
Upstream Culvert Invert	70.0
Downstream Culvert Invert	69.79
Culvert length	430.0
Upstream Est. SHWL Elev (ft-NAVD88)	75.1

(Tailwater from HY-8 Input in SFWMD ERP 141010-12, Converted to NAVD)

(From SFWMD ERP 141010-12, Converted to NAVD)

From DEM

Minimum slope

Measured from GIS, assume full R/W width

(Attained from SFWMD Permit Application 050613-21)

Existing Permitted Culvert Conveyance Size	2 - 24 inch x 38 inch
--	-----------------------

(Size information retrieved from SWFWMD Permit Application 141010-12)

Proposed Culvert Size	2 - 38 inch x 60 inch
-----------------------	-----------------------

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

PROJECT: CFX Feasibility Study: / Poinciana Parkway Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: JAN

DATE: 05/15/19
DATE: 05/15/19

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-4-01
------------------	---------

Total Contributing Flow Calculations

Existing Flow from EAST5WET =	554.47	(Node EAST5WET, 100-yr Storm)
Exist. Flow from Flood Study	584.05	(Links RRNORTH1 & RRNORTH2, 100-yr Storm)

(Contributing link flow attained from SWFWMD ERP App. 43023879)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	79.00	FEMA BFE
Roadway Crest Elevation	84.00	Assumed 5-ft above BFE
Upstream Culvert Invert	75.2	From DEM
Downstream Culvert Invert	75.00	Minimum slope
Culvert length	453.0	Measured from GIS, assume full R/W width
Upstream Est. SHWL Elev (ft-NAVD88)	77.0	NRCS Imagery estimate

Existing Permitted Culvert Conveyance Size	6 - 29 inch x 45 inch	In series upstream
--	-----------------------	--------------------

(size information retrieved from SWFWMD Permit Application 43023879)

Proposed Culvert Size	7 - 38 inch x 60 inch
-----------------------	-----------------------

(Size retrieved from HY-8 version 7.50)

PROJECT: CFX Feasibility Study: / Poinciana Parkway Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: JAN

DATE: 05/15/19
DATE: 05/15/19

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-4-02
------------------	---------

Total Contributing Flow Calculations

Exist. Flow from Flood Study	158.85	(100-yr Storm)	Node 17-92SE = 158.85 (cfs)
------------------------------	--------	----------------	-----------------------------

(Contributing link flow attained from SWFWMD ERP App. 43023879)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	73.00	(Tailwater from HY-8 Input in SWFWMD ERP 43023879.000)
Roadway Crest Elevation	79.00	Assumed 5-ft above crown
Upstream Culvert Invert	71.0	From DEM
Downstream Culvert Invert	68.80	Assumed slope
Culvert length	130.0	Measured from GIS, assumed extension of existing culvert
Upstream Est. SHWL Elev (ft-NAVD88)	78.5	Estimate based on NRCS soils

Existing Permitted Culvert Conveyance Size	10 feet x 3 feet
--	------------------

(Size information retrieved from US 17/US 92 FDOT Straight Line Diagram - Polk County [Road ID: 16050000])

Proposed Culvert Sizes	10 feet x 3 feet	&	48 inch
------------------------	------------------	---	---------

(Size retrieved from HY-8 version 7.50)

PROJECT: CFX Feasibility Study: / Poinciana Parkway Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: JAN

DATE: 05/15/19
DATE: 05/15/19

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-4-03
------------------	---------

Total Contributing Flow Calculations

Exist. Flow from Flood Study	613.05	(100-yr Storm)	Node 17-92NE = 613.05 (cfs)
------------------------------	--------	----------------	-----------------------------

(Contributing link flow attained from SWFWMD ERP App. 43023879)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	66.50	FEMA BFE
Roadway Crest Elevation	72.50	From DEM, Roadway Elevation
Upstream Culvert Invert	64.0	From DEM - assumed grade to culvert
Downstream Culvert Invert	63.90	Assumed slope
Culvert length	140.0	Measured from GIS, assume extension of existing culvert
Upstream Est. SHWL Elev (ft-NAVD88)		

Existing Permitted Culvert Conveyance Size	3 - 8 feet x 4 feet
--	---------------------

(Size information retrieved from US 17/US 92 FDOT Straight Line Diagram - Polk County [Road ID: 16050000])

Proposed Culvert Size	3 - 8 feet x 4 feet
-----------------------	---------------------

(Size retrieved from HY-8 version 7.50)

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-4-05A
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	47.9

Basin Runoff Calculations

Total Contributing Area (acres)	107.62
Pervious Contributing Area (acres)	107.62
Impervious Contributing Area (acres)	0.00
Weighted Runoff Coefficient ¹	0.36
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations

Event ²	25-year	Design	Base	Greatest
		50-year	100-year	500-yr
Intensity (in/hr) ³	4.42	4.87	5.40	N/A
Peak Flow (cfs)	156.87	188.57	217.93	321.00


(Used 500-year Log-Log graph to obtain basin runoff flow rate)

Solve for 500-year flow rate using log-log graph on the above 25, 50, and 100-year peak flow rates

$$y = Ax^{-B}$$

A = 73.596
 B = 0.237
 y = **321.00 cfs**
 x = 0.002


$$x = \sqrt[B]{\frac{A}{y}}$$



Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates, shown below.

$$x = \sqrt[B]{\frac{A}{y}}$$

A = 140.13
 B = 0.172
 y = 355.95
 x = 0.44%



Total Contributing Flow Calculations

Flow from Providence Development (cfs)	87.91
Total Design Peak Flow (cfs)	276.49
Total Base Peak Flow (cfs)	305.84
Total Greatest Peak Flow (cfs)	408.92

(25-yr/24-hr Storm) POND PN23-8 = 75.526 (cfs)
 POND RD-3B = 12.387 (cfs)
TOTAL = 87.913 (cfs)

(Contributing pond flows attained from SFWMD Permit Application 040220-40)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	80.47
Roadway Crest Elevation	88.37
Upstream Culvert Invert	80.37
Downstream Culvert Invert	80.27
Culvert length	550.0
Upstream Est. SHWL Elev (ft-NAVD88)	80.5

(Tailwater from SFWMD ERP 141010-12, Converted to NAVD)
 Assumed 5-ft above crown
 (Invert from SFWMD ERP 141010-12, Converted to NAVD)
 (Culvert slope from SFWMD ERP 141010-12)
 Measured from GIS, assume full R/W width
 (Attained from SFWMD Permit Application 141010-12)

Existing Permitted Culvert Conveyance Size	2 - 24 inch
--	-------------

(Size information retrieved from SWFWMD Permit Application 141010-12)

Proposed Culvert Size	6 - 36 inch
-----------------------	-------------

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-4-05B
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	25.6

Basin Runoff Calculations

Total Contributing Area (acres)	10.85
Pervious Contributing Area (acres)	10.85
Impervious Contributing Area (acres)	0.00
Weighted Runoff Coefficient ¹	0.36
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations

Event ²	25-year	Design	Base	Greatest
		50-year	100-year	500-yr
Intensity (in/hr) ³	6.00	6.57	7.30	N/A
Peak Flow (cfs)	21.49	25.67	29.70	43.35


(Used 500-year Log-Log graph to obtain basin runoff flow rate)

Solve for 500-year flow rate using log-log graph on the above 25, 50, and 100-year peak flow rates

$$y = Ax^{-B}$$

A = 10.189
 B = 0.233
 y = 43.35 cfs
 x = 0.002


$$x = \sqrt[B]{\frac{A}{y}}$$



Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates shown below.

$$x = \sqrt[B]{\frac{A}{y}}$$

A = 150.1
 B = 0.177
 y = 424.03
 x = 0.28%



Total Contributing Flow Calculations

Flow from CD-4-05A	276.49	(50-year)
	305.84	(100-year)
	408.92	(500-year)
Total Design Peak Flow (cfs)	302.16	
Total Base Peak Flow (cfs)	335.55	
Total Greatest Peak Flow (cfs)	452.27	

Cross Drain Sizing Calculations

Tailwater Elevation/Source	80.47	(Tailwater from SFWMD ERP 141010-12, Converted to NAVD)
Roadway Crest Elevation	87.00	Assumed 5-ft above crown
Upstream Culvert Invert	79.00	Assumed invert for crown of pipe at tailwater
Downstream Culvert Invert	78.83	Minimum slope
Culvert length	340.0	Measured from GIS, assume full R/W width
Upstream Est. SHWL Elev (ft-NAVD88)	77.5	(Attained from SFWMD Permit Application 070119-12)

Existing Permitted Culvert Conveyance Size	2 - 24 inch
--	-------------

(Size information retrieved from SWFWMD Permit Application 141010-12)

Proposed Culvert Size	6 - 36 inch
-----------------------	-------------

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

Table B.4 - Proposed Offsite Conveyance Calculations

Existing Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-4-06
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	72.1

Basin Runoff Calculations

Total Contributing Area (acres)	63.25
Pervious Contributing Area (acres)	63.25
Impervious Contributing Area (acres)	0.00
Weighted Runoff Coefficient ¹	0.36
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations

Event ²	25-year	Design 50-year	Base 100-year	Greatest 500-yr
Intensity (in/hr) ³	3.44	3.81	4.15	N/A
Peak Flow (cfs)	71.83	86.80	98.43	143.15

(Used 500-year Log-Log graph to obtain basin runoff flow rate)

Solve for 500-year flow rate using log-log graph on the above 25, 50, and 100-year peak flow rates



$$y = Ax^{-B}$$

A = 34.923
 B = 0.227
 y = **143.15 cfs**
 x = 0.002

Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates, shown below.

$$x = \sqrt[B]{\frac{A}{y}}$$

A = 53.135
 B = 0.183
 y = 208.04
 x = 0.06%



Total Contributing Flow Calculations

Flow from Natures Preserve Development (cfs)	22.92
Total Design Peak Flow (cfs)	109.72
Total Base Peak Flow (cfs)	121.35
Total Greatest Peak Flow (cfs)	166.07

(25-yr/72-hr Storm) POND 2 & 3 = 15.12 (cfs)
 POND4 = 2.60 (cfs)
 POND5 = 5.20 (cfs)
TOTAL = 22.92 (cfs)

(Contrib (Contributing pond flows attained from SFWMD Permit Application 101022-10))

Cross Drain Sizing Calculations

Tailwater Elevation/Source	76.07
Roadway Crest Elevation	79.77
Upstream Culvert Invert	73.71
Downstream Culvert Invert	72.59
Culvert length	480.0
Upstream Est. SHWL Elev (ft-NAVD88)	75.1

(Tailwater from HY-8 Input in SFWMD ERP 141010-12, Converted to NAVD)
 (From SFWMD ERP 141010-12, Converted to NAVD)
 From DEM
 Minimum slope
 Measured from GIS, assume full R/W width
 (Attained from SFWMD Permit Application 050613-21)

Existing Permitted Culvert Conveyance Size	2 - 24 inch x 38 inch
--	-----------------------

(Size information retrieved from SWFWMD Permit Application 141010-12)

Proposed Culvert Size	2 - 38 inch x 60 inch
-----------------------	-----------------------

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

PROJECT: CFX Feasibility Study: / Poinciana Parkway Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: JAN

DATE: 05/15/19
DATE: 05/15/19

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-5-01
------------------	---------

Total Contributing Flow Calculations

Exist. Flow from Flood Study	584.05	(100-yr Storm)	Links at RRNOTH = 584.05 (cfs)
------------------------------	--------	----------------	--------------------------------

(Contributing link flow attained from SWFWMD ERP App. 43023879)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	79.00	FEMA BFE
Roadway Crest Elevation	84.00	Assumed 5-ft above BFE
Upstream Culvert Invert	75.23	From DEM
Downstream Culvert Invert	75.00	Minimum slope
Culvert length	453.0	Measured from GIS, assume full R/W width
Upstream Est. SHWL Elev (ft-NAVD88)	77.0	NRCS Imagery estimate

Existing Permitted Culvert Conveyance Size	6 - 29 inch x 45 inch	In series upstream
--	-----------------------	--------------------

(size information retrieved from SWFWMD Permit Application 43023879)

Proposed Culvert Size	7 - 38 inch x 60 inch
-----------------------	-----------------------

(Size retrieved from HY-8 version 7.50)

PROJECT: CFX Feasibility Study: / Poinciana Parkway Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: JAN

DATE: 05/15/19
DATE: 05/15/19

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-5-02
------------------	---------

Total Contributing Flow Calculations

Exist. Flow from Flood Study	158.85	(100-yr Storm)	Node 17-92SE = 158.85 (cfs)
------------------------------	--------	----------------	-----------------------------

(Contributing link flow attained from SWFWMD ERP App. 43023879)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	73.00	FEMA BFE
Roadway Crest Elevation	79.00	Assumed 5-ft above crown
Upstream Culvert Invert	71.0	From DEM
Downstream Culvert Invert	68.80	Assumed slope
Culvert length	162.0	Measured from GIS, assume full R/W width
Upstream Est. SHWL Elev (ft-NAVD88)	66.0	Estimate based on NRCS soils

Existing Permitted Culvert Conveyance Size	10 feet x 3 feet
--	------------------

(Size information retrieved from US 17/US 92 FDOT Straight Line Diagram - Polk County [Road ID: 16050000])

Proposed Culvert Size	10 feet x 3 feet	&	48 inch
-----------------------	------------------	---	---------

(Size retrieved from HY-8 version 7.50)

PROJECT: CFX Feasibility Study: / Poinciana Parkway Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: JAN

DATE: 05/15/19
DATE: 05/15/19

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-5-03
------------------	---------

Total Contributing Flow Calculations

Exist. Flow from Flood Study	613.05	(100-yr Storm)	Node 17-92NE = 613.05 (cfs)
------------------------------	--------	----------------	-----------------------------

(Contributing link flow attained from SWFWMD ERP App. 43023879)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	66.50	FEMA BFE
Roadway Crest Elevation	72.50	From DEM, Roadway Elevation
Upstream Culvert Invert	64.0	From DEM - assumed grade to culvert
Downstream Culvert Invert	63.90	Assumed slope
Culvert length	140.0	Measured from GIS, assume extension of existing culvert
Upstream Est. SHWL Elev (ft-NAVD88)		

Existing Permitted Culvert Conveyance Size	3 - 8 feet x 4 feet
--	---------------------

(Size information retrieved from US 17/US 92 FDOT Straight Line Diagram - Polk County [Road ID: 16050000])

Proposed Culvert Size	3 - 8 feet x 4 feet
-----------------------	---------------------

(Size retrieved from HY-8 version 7.50)

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-5-05A
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	46.9

Basin Runoff Calculations

Total Contributing Area (acres)	106.40
Pervious Contributing Area (acres)	106.40
Impervious Contributing Area (acres)	0.00
Weighted Runoff Coefficient ¹	0.36
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations

		Design	Base	Greatest
Event ²	25-year	50-year	100-year	500-yr
Intensity (in/hr) ³	4.47	4.92	5.40	N/A
Peak Flow (cfs)	156.83	188.48	215.46	313.92


(Used 500-year Log-Log graph to obtain basin runoff flow rate)

Solve for 500-year flow rate using log-log graph on the above 25, 50, and 100-year peak flow rates

$$y = Ax^{-B}$$

A = 75.64
 B = 0.229
 y = **313.92 cfs**
 x = 0.002


$$x = \sqrt[B]{\frac{A}{y}}$$



Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates, shown below.

$$x = \sqrt[B]{\frac{A}{y}}$$

A = 143.89
 B = 0.165
 y = 323.23
 x = 0.74%



Total Contributing Flow Calculations

Flow from Providence Development (cfs)	87.91
Total Design Peak Flow (cfs)	276.39
Total Base Peak Flow (cfs)	303.37
Total Greatest Peak Flow (cfs)	401.83

(25-yr/24-hr Storm) POND PN23-8 = 75.526 (cfs)
 POND RD-3B = 12.387 (cfs)
TOTAL = 87.913 (cfs)

(Contributing pond flows attained from SFWMD Permit Application 040220-40)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	80.47
Roadway Crest Elevation	88.37
Upstream Culvert Invert	80.37
Downstream Culvert Invert	80.27
Culvert length	220.0
Upstream Est. SHWL Elev (ft-NAVD88)	80.5

(Tailwater from SFWMD ERP 141010-12, Converted to NAVD)
 Assumed 5-ft above crown
 Assumed invert for crown of pipe at tailwater
 Assumed slope
 Measured from GIS, assume full R/W width
 (Attained from SFWMD Permit Application 141010-12)

Existing Permitted Culvert Conveyance Size	2 - 24 inch
--	-------------

In series upstream

(Size information retrieved from SWFWMD Permit Application 141010-12)

Proposed Culvert Size	4 - 36 inch
-----------------------	-------------

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-5-05B
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	40.6

Basin Runoff Calculations

Total Contributing Area (acres)	41.34
Pervious Contributing Area (acres)	41.34
Impervious Contributing Area (acres)	0.00
Weighted Runoff Coefficient ¹	0.36
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations


Event ²	25-year	50-year	Base 100-year	Greatest 500-yr
Intensity (in/hr) ³	4.83	5.31	5.90	N/A
Peak Flow (cfs)	65.86	79.02	91.46	134.79

(Used 500-year Log-Log graph to obtain basin runoff flow rate)

Solve for 500-year flow rate using log-log graph on the above 25, 50, and 100-year peak flow rates

$$y = Ax^{-B}$$


A = 30.904
 B = 0.237
 y = **134.79 cfs**
 x = 0.002



Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates shown below.

$$x = \sqrt[B]{\frac{A}{y}}$$

A = 173.63
 B = 0.181
 y = 413.09
 x = 0.83%



Total Contributing Flow Calculations

Flows from CD-5-05A	276.39	(50-year)
	303.37	(100-year)
	401.83	(500-year)
Total Design Peak Flow (cfs)	355.42	
Total Base Peak Flow (cfs)	394.84	
Total Greatest Peak Flow (cfs)	536.62	

Cross Drain Sizing Calculations

Tailwater Elevation/Source	80.47	(Tailwater from SFWMD ERP 141010-12, Converted to NAVD)
Roadway Crest Elevation	87.00	Assumed 5-ft above crown
Upstream Culvert Invert	79.0	Assumed invert for crown of pipe at tailwater
Downstream Culvert Invert	78.83	Minimum slope
Culvert length	344.0	Measured from GIS, assume full R/W width
Upstream Est. SHWL Elev (ft-NAVD88)	74.0	Estimate based on NRCS soils

Existing Permitted Culvert Conveyance Size	2 - 24 inch	In series upstream
--	-------------	--------------------

(Size information retrieved from SFWMD Permit Application 141010-12)

Proposed Culvert Size	6 - 36 inch
-----------------------	--------------------

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-5-06
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	72.7

Basin Runoff Calculations

Total Contributing Area (acres)	64.02
Pervious Contributing Area (acres)	64.02
Impervious Contributing Area (acres)	0.00
Weighted Runoff Coefficient ¹	0.36
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations

Event ²	25-year	Design	Base	Greatest
		50-year	100-year	500-yr
Intensity (in/hr) ³	3.42	3.79	4.20	N/A
Peak Flow (cfs)	72.31	87.40	100.83	149.63


(Used 500-year Log-Log graph to obtain basin runoff flow rate)

Solve for 500-year flow rate using log-log graph on the above 25, 50, and 100-year peak flow rates

$$y = Ax^{-B}$$

A = 33.671
 B = 0.24
 y = 149.63 cfs
 x = 0.002


$$x = \sqrt[B]{\frac{A}{y}}$$



Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates shown below.

$$x = \sqrt[B]{\frac{A}{y}}$$

A = 45.887
 B = 0.209
 y = 172.92
 x = 0.18%



Total Contributing Flow Calculations

Flow from Natures Preserve Development (cfs)	22.92
Total Design Peak Flow (cfs)	110.32
Total Base Peak Flow (cfs)	123.75
Total Greatest Peak Flow (cfs)	172.55

(25-yr/72-hr Storm)
 POND 2 & 3 = 15.12 (cfs)
 POND4 = 2.60 (cfs)
 POND5 = 5.20 (cfs)
 TOTAL = 22.92 (cfs)

(Contributing pond flows attained from SFWMD Permit Application 101022-10)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	76.07
Roadway Crest Elevation	79.77
Upstream Culvert Invert	73.7
Downstream Culvert Invert	72.59
Culvert length	849.0
Upstream Est. SHWL Elev (ft-NAVD88)	75.1

(Tailwater from HY-8 Input in SFWMD ERP 141010-12, Converted to NAVD)
 (From SFWMD ERP 141010-12, Converted to NAVD)
 From DEM
 Minimum slope
 Measured from GIS, assume full R/W width
 (Attained from SFWMD Permit Application 050613-21)

Proposed Culvert Size	2 - 24 inch x 38 inch
-----------------------	-----------------------

(Size information retrieved from SWFWMD Permit Application 141010-12)

Required Minimum Size	2 - 38 inch x 60 inch
-----------------------	-----------------------

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

Table B.4 - Proposed Offsite Conveyance Calculations

Proposed Cross Drain at Poinciana Pkwy Extension

Cross Drain Name	CD-5B-05B
Precipitation Zone	8
Pervious C-Value ¹	0.3
Impervious C-value	0.95
Time of Concentration (min)	80.1

Basin Runoff Calculations

Total Contributing Area (acres)	86.96
Pervious Contributing Area (acres)	86.96
Impervious Contributing Area (acres)	0.00
Weighted Runoff Coefficient ¹	0.36
Design Event ²	50-year

Frequency Factor = 1.1 for 25-yr, 1.2 for 50-yr, 1.25 for 100-yr

Rational Method Peak Flow Rate Calculations

Event ²	25-year	Design 50-year	Base 100-year	Greatest 500-yr
Intensity (in/hr) ³	3.21	3.56	3.75	N/A
Peak Flow (cfs)	91.98	111.34	122.29	172.53


(Used 500-year Log-Log graph to obtain basin runoff flow rate)

Solve for 500-year flow rate using log-log graph on the above 25, 50, and 100-year peak flow rates

$$y = Ax^{-B}$$

A = 48.259
 B = 0.205
 y = **172.53 cfs**
 x = 0.002


$$x = \sqrt[B]{\frac{A}{y}}$$



Solve for probability of overtopping using log-log graph based on 50, 100, and 500-year total peak flow rates shown below.

$$x = \sqrt[B]{\frac{A}{y}}$$

A = 68.828
 B = 0.167
 y = 229.18
 x = 0.07%



Total Contributing Flow Calculations

Flow from Natures Preserve Development (cfs)	22.92
Total Design Peak Flow (cfs)	134.26
Total Base Peak Flow (cfs)	145.21
Total Greatest Peak Flow (cfs)	195.45

(25-yr/72-hr Storm)

POND 2 & 3 = 15.12 (cfs)
 POND4 = 2.60 (cfs)
 POND5 = 5.20 (cfs)
 TOTAL = 22.92 (cfs)

(Contributing pond flows attained from SFWMD Permit Application 101022-10)

Cross Drain Sizing Calculations

Tailwater Elevation/Source	76.07
Roadway Crest Elevation	79.77
Upstream Culvert Invert	73.7
Downstream Culvert Invert	72.59
Culvert length	335.0
Upstream Est. SHWL Elev (ft-NAVD88)	74.0

(Tailwater from HY-8 Input in SFWMD ERP 141010-12, Converted to NAVD)
 (From SFWMD ERP 141010-12, Converted to NAVD)
 From DEM
 Minimum slope
 Measured from GIS, assume full R/W width
 Estimate based on NRCS soils

Existing Permitted Culvert Conveyance Size	2 - 24 inch x 38 inch
--	-----------------------

(Size information retrieved from SWFWMD Permit Application 141010-12)

Proposed Culvert Size	2 - 38 inch x 60 inch
-----------------------	-----------------------

(Size retrieved from HY-8 version 7.50)

Notes:

¹ Pervious Runoff Coefficients value assumed to be the max of Pasture/Grass with poorly drained soils at 2-7% slope. Frequency Factor applied per Design Storm Event (Tables B-4 & B-5, FDOT Drainage Design Guide, January 2017).

² Per FDOT Drainage Manual, 50-year considered design event for mainline interstates and 100-year used if culvert proposed within regulated floodway.

³ Design Intensity calculated from FDOT IDF Regression Equations for Tc < 180 minutes. If Tc > 180 minutes, intensity estimated directly from the IDF Curve.

PROJECT: CFX Feasibility Study: **PREPARED:** MDP **DATE:** 03/05/19
I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola and Polk County, Florida **CHECKED:** ALE **DATE:** 05/13/19

Table B.5 - Proposed Time of Concentration Summary

Cross Drain ID	Time of Concentration (min)
CD-1-03	30.1
CD-1-04	93.1
CD-1-05	18.7
CD-1-06	23.2
CD-1-07	42.7
CD-1-08	70.0
CD-4-05A	47.9
CD-4-05B	25.6
CD-4-06	72.1
CD-5-05A	46.9
CD-5-05B	40.6
CD-5-06	72.7
CD-5B-05B	80.1

PROJECT: CFX Feasibility Study: _____ **PREPARED:** MDP _____ **DATE:** 03/05/19 _____
 I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola and Polk County, Florida _____ **CHECKED:** ALE _____ **DATE:** 05/13/19 _____

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or DEVELOPED / UNDEVELOPED BASIN: CD-1-03
Tc -- Tt (through subarea)

L = 1,799 ft

Sheet flow (Applicable to Tc only)

Segment ID	AB
1. Surface description [†]	Range
2. Mannings roughness coeff., n †	0.13
3. Flow length, L (total L ≤ 100 ft.)	100
4. 2-year, 24-hour rainfall (in.) ††	4.8
5. Land slope, s (ft./ft.)	0.043
6. Compute Tt in hr, $Tt = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ †††	0.087
Subtotal	0.09

Shallow Concentrated Flow

Segment ID	BC
7. Surface description (Paved or Unpaved)	Unpaved
8. Flow length, L (ft)	1,699
9. Watercourse slope, s (ft/ft)	0.005
10. Average velocity ^{†††} , $V = kS^{0.5}$ (fps)	1.14
11. Compute Tt in hr, $Tt = L/3600V$	0.41
Subtotal	0.41

Time of Concentration, hr. (summation of subtotals)

Hours	0.50
Minutes	30.1
Total	30.1

Notes:

- † Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
- †† The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
- ††† This equation is derived from TR-55

PROJECT: CFX Feasibility Study: _____ **PREPARED:** MDP _____ **DATE:** 03/05/19 _____
 I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola and Polk County, Florida _____ **CHECKED:** ALE _____ **DATE:** 05/13/19 _____

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or DEVELOPED / UNDEVELOPED BASIN: CD-1-04
Tc -- Tt (through subarea)

L = 6,147 ft

Sheet flow (Applicable to Tc only)

- Segment ID
- 1. Surface description[†]
- 2. Mannings roughness coeff., n [†]
- 3. Flow length, L (total L ≤ 100 ft.)
- 4. 2-year, 24-hour rainfall (in.) ^{††}
- 5. Land slope, s (ft./ft.)
- 6. Compute Tt in hr, $Tt = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ ^{†††}
- Subtotal

AB
Fallow/Range
0.122
100
4.8
0.049
0.079
0.08

Shallow Concentrated Flow

- Segment ID
- 7. Surface description (Paved or Unpaved)
- 8. Flow length, L (ft)
- 9. Watercourse slope, s (ft/ft)
- 10. Average velocity^{†††}, $V = kS^{0.5}$ (fps)
- 11. Compute Tt in hr, $Tt = L/3600V$
- Subtotal

BC
Unpaved
6,047
0.005
1.14
1.47
1.47

Time of Concentration, hr. (summation of subtotals)

Hours	1.55
Minutes	93.1
Total	93.1

Notes:

[†] Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
^{††} The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
^{†††} This equation is derived from TR-55

PROJECT: CFX Feasibility Study: _____ **PREPARED:** MDP _____ **DATE:** 03/05/19 _____
 I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola and Polk County, Florida _____ **CHECKED:** ALE _____ **DATE:** 05/13/19 _____

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or DEVELOPED / UNDEVELOPED BASIN: CD-1-05
Tc -- Tt (through subarea)

L = 1,127 ft

Sheet flow (Applicable to Tc only)

Segment ID

1. Surface description[†]
 2. Mannings roughness coeff., n [†]
 3. Flow length, L (total L ≤ 100 ft.)
 4. 2-year, 24-hour rainfall (in.) ^{††}
 5. Land slope, s (ft./ft.)
 6. Compute Tt in hr, $Tt = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ ^{†††}
- Subtotal

AB
Smooth Surfaces/Light Underbrush
0.152
100
4.8
0.062
0.086
0.09

Shallow Concentrated Flow

Segment ID

7. Surface description (Paved or Unpaved)
 8. Flow length, L (ft)
 9. Watercourse slope, s (ft/ft)
 10. Average velocity^{†††}, V = kS^{0.5} (fps)
 11. Compute Tt in hr, Tt = L/3600V
- Subtotal

BC
Unpaved
1,027
0.006
1.26
0.23
0.23

Time of Concentration, hr. (summation of subtotals)

Hours	0.31
Minutes	18.7
Total	18.7

Notes:

- † Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
- †† The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
- ††† This equation is derived from TR-55

PROJECT: CFX Feasibility Study:
 I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: ALE

DATE: 03/05/19
DATE: 05/13/19

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or DEVELOPED / UNDEVELOPED BASIN: CD-1-06
Tc -- Tt (through subarea)

L = 1,110 ft

Sheet flow (Applicable to Tc only)

Segment ID

1. Surface description[†]
2. Mannings roughness coeff., n[†]
3. Flow length, L (total L ≤ 100 ft.)
4. 2-year, 24-hour rainfall (in.)^{††}
5. Land slope, s (ft./ft.)
6. Compute Tt in hr, $Tt = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ ^{†††}
- Subtotal

AB
Smooth Surfaces/Range
0.119
100
4.8
0.005
0.193
0.19

Shallow Concentrated Flow

Segment ID

7. Surface description (Paved or Unpaved)
8. Flow length, L (ft)
9. Watercourse slope, s (ft/ft)
10. Average velocity^{†††}, $V = kS^{0.5}$ (fps)
11. Compute Tt in hr, $Tt = L/3600V$
- Subtotal

BC
Unpaved
1,010
0.008
1.45
0.19
0.19

Time of Concentration, hr. (summation of subtotals)

Hours	0.39
Minutes	23.2
Total	23.2

Notes:

[†] Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
^{††} The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
^{†††} This equation is derived from TR-55

PROJECT: CFX Feasibility Study:
I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: ALE

DATE: 03/05/19
DATE: 05/13/19

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or DEVELOPED / UNDEVELOPED BASIN: CD-1-07
Tc -- Tt (through subarea)

L = 2,916 ft

Sheet flow (Applicable to Tc only)

- Segment ID
1. Surface description[†]
2. Mannings roughness coeff., n [†]
3. Flow length, L (total L ≤ 100 ft.)
4. 2-year, 24-hour rainfall (in.) ^{††}
5. Land slope, s (ft./ft.)
6. Compute Tt in hr, $Tt = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ ^{†††}
Subtotal

AB
Smooth Surfaces
0.011
100
4.8
0.006
0.026
0.03

Shallow Concentrated Flow

- Segment ID
7. Surface description (Paved or Unpaved)
8. Flow length, L (ft)
9. Watercourse slope, s (ft/ft)
10. Average velocity^{†††}, $V = kS^{0.5}$ (fps)
11. Compute Tt in hr, $Tt = L/3600V$
Subtotal

BC
Unpaved
2,816
0.005
1.14
0.69
0.69

Time of Concentration, hr. (summation of subtotals)

Hours	0.71
Minutes	42.7
Total	42.7

Notes:

[†] Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
^{††} The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
^{†††} This equation is derived from TR-55

PROJECT: CFX Feasibility Study:
I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: ALE

DATE: 03/05/19
DATE: 05/13/19

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or DEVELOPED / UNDEVELOPED BASIN: CD-1-08
Tc or Tt (through subarea)

L = 4,831 ft

Sheet flow (Applicable to Tc only)

- Segment ID
- 1. Surface description[†]
- 2. Mannings roughness coeff., n [†]
- 3. Flow length, L (total L ≤ 100 ft.)
- 4. 2-year, 24-hour rainfall (in.) ^{††}
- 5. Land slope, s (ft./ft.)
- 6. Compute Tt in hr, $Tt = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ ^{†††}
- Subtotal

AB
Smooth Surfaces
0.011
100
4.8
0.023
0.016
0.02

Shallow Concentrated Flow

- Segment ID
- 7. Surface description (Paved or Unpaved)
- 8. Flow length, L (ft)
- 9. Watercourse slope, s (ft/ft)
- 10. Average velocity^{†††}, $V = kS^{0.5}$ (fps)
- 11. Compute Tt in hr, $Tt = L/3600V$
- Subtotal

BC
Unpaved
4,731
0.005
1.14
1.15
1.15

Time of Concentration, hr. (summation of subtotals)

Hours	1.17
Minutes	70.0
Total	70.0

Notes:

[†] Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
^{††} The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
^{†††} This equation is derived from TR-55

PROJECT: CFX Feasibility Study:
I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola County, Florida

PREPARED: MDP
CHECKED: ALE

DATE: 03/05/19
DATE: 05/13/19

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or DEVELOPED / UNDEVELOPED BASIN: CD-4-05A
Tc or Tt (through subarea)

L = 3,269 ft

Sheet flow (Applicable to Tc only)

- Segment ID
- 1. Surface description[†]
- 2. Mannings roughness coeff., n[†]
- 3. Flow length, L (total L ≤ 100 ft.)
- 4. 2-year, 24-hour rainfall (in.)^{††}
- 5. Land slope, s (ft./ft.)
- 6. Compute Tt in hr, $Tt = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ ^{†††}
- Subtotal

AB
Smooth Surfaces
0.011
100
4.8
0.006
0.026
0.03

Shallow Concentrated Flow

- Segment ID
- 7. Surface description (Paved or Unpaved)
- 8. Flow length, L (ft)
- 9. Watercourse slope, s (ft/ft)
- 10. Average velocity^{†††}, $V = kS^{0.5}$ (fps)
- 11. Compute Tt in hr, $Tt = L/3600V$
- Subtotal

BC
Unpaved
3,169
0.005
1.14
0.77
0.77

Time of Concentration, hr. (summation of subtotals)

Hours	0.80
Minutes	47.9
Total	47.9

Notes:

† Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
 †† The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
 ††† This equation is derived from TR-55

PROJECT: CFX Feasibility Study:
I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola County, Florida

PREPARED: MDP
CHECKED: ALE

DATE: 03/05/19
DATE: 05/13/19

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or DEVELOPED / UNDEVELOPED BASIN: CD-4-05B
Tc or Tt (through subarea)

L = 1,454 ft

Sheet flow (Applicable to Tc only)

- Segment ID
- 1. Surface description[†]
- 2. Mannings roughness coeff., n[†]
- 3. Flow length, L (total L ≤ 100 ft.)
- 4. 2-year, 24-hour rainfall (in.)^{††}
- 5. Land slope, s (ft./ft.)
- 6. Compute Tt in hr, $Tt = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ ^{†††}
- Subtotal

AB
Fallow
0.05
100
4.8
0.005
0.096
0.10

Shallow Concentrated Flow

- Segment ID
- 7. Surface description (Paved or Unpaved)
- 8. Flow length, L (ft)
- 9. Watercourse slope, s (ft/ft)
- 10. Average velocity^{†††}, $V = kS^{0.5}$ (fps)
- 11. Compute Tt in hr, $Tt = L/3600V$
- Subtotal

BC
Unpaved
1,354
0.005
1.14
0.33
0.33

Time of Concentration, hr. (summation of subtotals)

Hours	0.43
Minutes	25.6
Total	25.6

Notes:

† Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
 †† The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
 ††† This equation is derived from TR-55

PROJECT: CFX Feasibility Study:
I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola County, Florida

PREPARED: MDP
CHECKED: ALE

DATE: 03/05/19
DATE: 05/13/19

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or **DEVELOPED / UNDEVELOPED** BASIN: CD-4-06
Tc or **Tt (through subarea)**

L = 4,973 ft

Sheet flow (Applicable to Tc only)

- Segment ID
 1. Surface description[†]
 2. Mannings roughness coeff., n[†]
 3. Flow length, L (total L ≤ 100 ft.)
 4. 2-year, 24-hour rainfall (in.)^{††}
 5. Land slope, s (ft./ft.)
 6. Compute Tt in hr, $Tt = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ ^{†††}
 Subtotal

AB
Smooth Surfaces
0.011
100
4.8
0.023
0.016
0.02

Shallow Concentrated Flow

- Segment ID
 7. Surface description (Paved or Unpaved)
 8. Flow length, L (ft)
 9. Watercourse slope, s (ft/ft)
 10. Average velocity^{†††}, $V = kS^{0.5}$ (fps)
 11. Compute Tt in hr, $Tt = L/3600V$
 Subtotal

BC
Unpaved
4,873
0.005
1.14
1.19
1.19

Time of Concentration, hr. (summation of subtotals)

Hours	1.20
Minutes	72.1
Total	72.1

Notes:

[†] Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
^{††} The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
^{†††} This equation is derived from TR-55

PROJECT: CFX Feasibility Study:
I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: ALE

DATE: 03/05/19
DATE: 05/13/19

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or DEVELOPED / UNDEVELOPED BASIN: CD-5-05A
Tc or Tt (through subarea)

L = 3,216 ft

Sheet flow (Applicable to Tc only)

- Segment ID
- 1. Surface description[†]
- 2. Mannings roughness coeff., n [†]
- 3. Flow length, L (total L ≤ 100 ft.)
- 4. 2-year, 24-hour rainfall (in.) ^{††}
- 5. Land slope, s (ft./ft.)
- 6. Compute Tt in hr, $Tt = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ ^{†††}
- Subtotal

AB
Smooth Surfaces
0.011
100
4.8
0.006
0.026
0.03

Shallow Concentrated Flow

- Segment ID
- 7. Surface description (Paved or Unpaved)
- 8. Flow length, L (ft)
- 9. Watercourse slope, s (ft/ft)
- 10. Average velocity^{†††}, $V = kS^{0.5}$ (fps)
- 11. Compute Tt in hr, $Tt = L/3600V$
- Subtotal

BC
Unpaved
3,116
0.005
1.15
0.76
0.76

Time of Concentration, hr. (summation of subtotals)

Hours	0.78
Minutes	46.9
Total	46.9

Notes:

† Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
 †† The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
 ††† This equation is derived from TR-55

PROJECT: CFX Feasibility Study:
I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola and Polk County, Florida

PREPARED: MDP
CHECKED: ALE

DATE: 03/05/19
DATE: 05/13/19

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or DEVELOPED / UNDEVELOPED BASIN: CD-5-05B
Tc or Tt (through subarea)

L = 2,491 ft

Sheet flow (Applicable to Tc only)

- Segment ID
- 1. Surface description[†]
- 2. Mannings roughness coeff., n [†]
- 3. Flow length, L (total L ≤ 100 ft.)
- 4. 2-year, 24-hour rainfall (in.) ^{††}
- 5. Land slope, s (ft./ft.)
- 6. Compute Tt in hr, $Tt = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ ^{†††}
- Subtotal

AB
Fallow
0.05
100
4.8
0.005
0.096
0.10

Shallow Concentrated Flow

- Segment ID
- 7. Surface description (Paved or Unpaved)
- 8. Flow length, L (ft)
- 9. Watercourse slope, s (ft/ft)
- 10. Average velocity^{†††}, $V = kS^{0.5}$ (fps)
- 11. Compute Tt in hr, $Tt = L/3600V$
- Subtotal

BC
Unpaved
2,391
0.005
1.15
0.58
0.58

Time of Concentration, hr. (summation of subtotals)

Hours	0.68
Minutes	40.6
Total	40.6

Notes:

† Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
 †† The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
 ††† This equation is derived from TR-55

PROJECT: CFX Feasibility Study:
I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola County, Florida

PREPARED: MDP
CHECKED: ALE

DATE: 03/05/19
DATE: 05/13/19

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or DEVELOPED / UNDEVELOPED BASIN: CD-5-06
Tc or Tt (through subarea)

L = 5,013 ft

Sheet flow (Applicable to Tc only)

- Segment ID
- 1. Surface description[†]
- 2. Mannings roughness coeff., n [†]
- 3. Flow length, L (total L ≤ 100 ft.)
- 4. 2-year, 24-hour rainfall (in.) ^{††}
- 5. Land slope, s (ft./ft.)
- 6. Compute Tt in hr, $Tt = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ ^{†††}
- Subtotal

AB
Smooth Surfaces
0.011
100
4.8
0.023
0.016
0.02

Shallow Concentrated Flow

- Segment ID
- 7. Surface description (Paved or Unpaved)
- 8. Flow length, L (ft)
- 9. Watercourse slope, s (ft/ft)
- 10. Average velocity^{†††}, $V = kS^{0.5}$ (fps)
- 11. Compute Tt in hr, $Tt = L/3600V$
- Subtotal

BC
Unpaved
4,913
0.005
1.14
1.20
1.20

Time of Concentration, hr. (summation of subtotals)

Hours	1.21
Minutes	72.7
Total	72.7

Notes:

- † Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
- †† The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
- ††† This equation is derived from TR-55

PROJECT: CFX Feasibility Study:
I-4 / Poinciana Parkway Connector Extension
LOCATION: Osceola County, Florida

PREPARED: MDP
CHECKED: ALE

DATE: 03/05/19
DATE: 05/13/19

Table B.6 - Proposed Offsite Time of Concentration Calculations

PROPOSED or DEVELOPED / UNDEVELOPED BASIN: CD-5B-05B
T_c or T_t (through subarea)

L = 5,519 ft

Sheet flow (Applicable to T_c only)

- Segment ID
- 1. Surface description[†]
- 2. Mannings roughness coeff., n [†]
- 3. Flow length, L (total L ≤ 100 ft.)
- 4. 2-year, 24-hour rainfall (in.) ^{††}
- 5. Land slope, s (ft./ft.)
- 6. Compute T_t in hr, $T_t = [0.007(nL)^{0.8}] / [P_{24hr}^{0.5} s^{0.4}]$ ^{†††}
- Subtotal

AB
Smooth Surfaces
0.011
100
4.8
0.023
0.016
0.02

Shallow Concentrated Flow

- Segment ID
- 7. Surface description (Paved or Unpaved)
- 8. Flow length, L (ft)
- 9. Watercourse slope, s (ft/ft)
- 10. Average velocity^{†††}, $V = kS^{0.5}$ (fps)
- 11. Compute T_t in hr, $T_t = L/3600V$
- Subtotal

BC
Unpaved
5,419
0.005
1.14
1.32
1.32

Time of Concentration, hr. (summation of subtotals)

Hours	1.33
Minutes	80.1
Total	80.1

Notes:

† Values from Table 3-1 of Urban Hydrology for Small Watersheds, Technical Release of TR-55
 †† The 2-year, 24-hour rainfall was used based on TR-55 Figure B-3.
 ††† This equation is derived from TR-55

HY-8 Culvert Analysis Report

Crossing Discharge Data

Discharge Selection Method: User Defined

Table 1 - Summary of Culvert Flows at Crossing: CD-1-01 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-1-01 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
83.11	EAST5WET	554.47	554.47	0.00	1
83.23	RRNORTH	584.05	584.05	0.00	1
87.00	Overtopping	1179.04	1179.04	0.00	Overtopping

Rating Curve Plot for Crossing: CD-1-01 POST

Total Rating Curve

Crossing: CD-1-01 POST




Table 2 - Culvert Summary Table: CD-1-01 POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
EAST5WET	554.47	554.47	83.11	2.994	5.106	4-FFf	3.167	1.965	3.167	4.180	4.824
RRNORTH	584.05	584.05	83.23	3.109	5.227	4-FFf	3.167	2.020	3.167	4.180	5.082

Straight Culvert
Inlet Elevation (invert): 78.00 ft, Outlet Elevation (invert): 77.82 ft
Culvert Length: 358.00 ft, Culvert Slope: 0.0005

Culvert Performance Curve Plot: CD-1-01 POST

Performance Curve


Culvert: CD-1-01 POST



Water Surface Profile Plot for Culvert: CD-1-01 POST

Crossing - CD-1-01 POST, Design Discharge - 584.0 cfs

Culvert - CD-1-01 POST, Culvert Discharge - 584.0 cfs



Site Data - CD-1-01 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 78.00 ft

Outlet Station: 358.00 ft

Outlet Elevation: 77.82 ft

Number of Barrels: 9

Culvert Data Summary - CD-1-01 POST

Barrel Shape: Elliptical

Barrel Span: 60.00 in

Barrel Rise: 38.00 in

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 3 - Downstream Channel Rating Curve (Crossing: CD-1-01 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
554.47	82.00	4.18
584.05	82.00	4.18

Tailwater Channel Data - CD-1-01 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 82.00 ft

Roadway Data for Crossing: CD-1-01 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 87.00 ft

Roadway Surface: Paved

Roadway Top Width: 189.00 ft

Crossing Discharge Data

Discharge Selection Method: User Defined

Table 4 - Summary of Culvert Flows at Crossing: CD-1-02 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-1-02 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
85.15	RRSOUTH	153.47	153.47	0.00	1
85.15	RRSOUTH	153.47	153.47	0.00	1
90.00	Overtopping	872.29	872.29	0.00	Overtopping

Rating Curve Plot for Crossing: CD-1-02 POST

Total Rating Curve

Crossing: CD-1-02 POST




Table 5 - Culvert Summary Table: CD-1-02 POST

Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
RRSOUTH	153.47	153.47	85.15	2.386	5.155	4-FFf	2.735	1.723	5.000	5.000	1.954
RRSOUTH	153.47	153.47	85.15	2.386	5.155	4-FFf	2.735	1.723	5.000	5.000	1.954

Straight Culvert


Inlet Elevation (invert): 80.00 ft, Outlet Elevation (invert): 79.82 ft

Culvert Length: 358.00 ft, Culvert Slope: 0.0005

Culvert Performance Curve Plot: CD-1-02 POST

Performance Curve


Culvert: CD-1-02 POST



Water Surface Profile Plot for Culvert: CD-1-02 POST

Crossing - CD-1-02 POST, Design Discharge - 153.5 cfs

Culvert - CD-1-02 POST, Culvert Discharge - 153.5 cfs



Site Data - CD-1-02 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 80.00 ft

Outlet Station: 358.00 ft

Outlet Elevation: 79.82 ft

Number of Barrels: 4

Culvert Data Summary - CD-1-02 POST

Barrel Shape: Circular

Barrel Diameter: 5.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 6 - Downstream Channel Rating Curve (Crossing: CD-1-02 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
153.47	85.00	5.00
153.47	85.00	5.00

Tailwater Channel Data - CD-1-02 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 85.00 ft

Roadway Data for Crossing: CD-1-02 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 90.00 ft

Roadway Surface: Paved

Roadway Top Width: 160.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 7 - Summary of Culvert Flows at Crossing: CD-1-03 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-1-03 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
94.08	50 year	124.79	124.79	0.00	1
94.55	100 year	137.19	137.19	0.00	1
96.20	500 year	182.18	182.18	0.00	1
98.10	Overtopping	227.58	227.58	0.00	Overtopping

Rating Curve Plot for Crossing: CD-1-03 POST

Total Rating Curve

Crossing: CD-1-03 POST





Table 8 - Culvert Summary Table: CD-1-03 POST

Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	124.79	124.79	94.08	3.914	3.979	7-M2c	3.000	2.377	2.377	0.870	8.749
100 year	137.19	137.19	94.55	4.254	4.453	7-M2c	3.000	2.532	2.532	0.870	9.030
500 year	182.18	182.18	96.20	5.678	6.103	6-FFc	3.000	3.000	3.000	0.870	10.121

Straight Culvert
Inlet Elevation (invert): 90.10 ft, Outlet Elevation (invert): 89.82 ft
Culvert Length: 222.00 ft, Culvert Slope: 0.0013


Culvert Performance Curve Plot: CD-1-03 POST



Water Surface Profile Plot for Culvert: CD-1-03 POST

Crossing - CD-1-03 POST, Design Discharge - 182.2 cfs

Culvert - CD-1-03 POST, Culvert Discharge - 182.2 cfs



Site Data - CD-1-03 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 90.10 ft

Outlet Station: 222.00 ft

Outlet Elevation: 89.82 ft

Number of Barrels: 1

Culvert Data Summary - CD-1-03 POST

Barrel Shape: Concrete Box

Barrel Span: 6.00 ft

Barrel Rise: 3.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: 1:1 Bevel Headwall

Inlet Depression: None

Table 9 - Downstream Channel Rating Curve (Crossing: CD-1-03 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
124.79	90.97	0.87
137.19	90.97	0.87
182.18	90.97	0.87

Tailwater Channel Data - CD-1-03 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 90.97 ft

Roadway Data for Crossing: CD-1-03 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 98.10 ft

Roadway Surface: Paved

Roadway Top Width: 149.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 10 - Summary of Culvert Flows at Crossing: CD-1-04 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-1-04 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
91.09	50 year	415.35	415.35	0.00	1
91.35	100 year	442.33	442.33	0.00	1
92.73	500 year	552.29	552.29	0.00	1
95.50	Overtopping	739.88	739.88	0.00	Overtopping

Rating Curve Plot for Crossing: CD-1-04 POST

Total Rating Curve

Crossing: CD-1-04 POST




Table 11 - Culvert Summary Table: CD-1-04 POST

Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	415.35	415.35	91.09	4.233	4.592	7-M2c	4.000	2.759	2.759	0.570	8.986
100 year	442.33	442.33	91.35	4.444	4.851	7-M2c	4.000	2.848	2.848	0.570	9.243
500 year	552.29	552.29	92.73	5.422	6.226	7-M2c	4.000	3.173	3.173	0.570	10.332

Straight Culvert


Inlet Elevation (invert): 86.50 ft, Outlet Elevation (invert): 86.00 ft

Culvert Length: 342.00 ft, Culvert Slope: 0.0015

Culvert Performance Curve Plot: CD-1-04 POST

Performance Curve


Culvert: CD-1-04 POST



Water Surface Profile Plot for Culvert: CD-1-04 POST

Crossing - CD-1-04 POST, Design Discharge - 552.3 cfs

Culvert - CD-1-04 POST, Culvert Discharge - 552.3 cfs



Site Data - CD-1-04 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 86.50 ft

Outlet Station: 342.00 ft

Outlet Elevation: 86.00 ft

Number of Barrels: 5

Culvert Data Summary - CD-1-04 POST

Barrel Shape: Circular

Barrel Diameter: 4.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Beveled Edge (1:1)

Inlet Depression: None

Table 12 - Downstream Channel Rating Curve (Crossing: CD-1-04 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
415.35	87.07	0.57
442.33	87.07	0.57
552.29	87.07	0.57

Tailwater Channel Data - CD-1-04 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 87.07 ft

Roadway Data for Crossing: CD-1-04 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 95.50 ft

Roadway Surface: Paved

Roadway Top Width: 172.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 13 - Summary of Culvert Flows at Crossing: CD-1-05 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-1-05 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
89.79	50 year	109.50	109.50	0.00	1
89.93	100 year	115.06	115.06	0.00	1
90.65	500 year	135.92	135.92	0.00	1
94.50	Overtopping	221.92	221.92	0.00	Overtopping

Rating Curve Plot for Crossing: CD-1-05 POST

Total Rating Curve

Crossing: CD-1-05 POST




Table 14 - Culvert Summary Table: CD-1-05 POST

Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	109.50	109.50	89.79	2.950	3.287	7-M2c	3.000	1.960	1.960	1.070	7.459
100 year	115.06	115.06	89.93	3.054	3.429	7-M2c	3.000	2.010	2.010	1.070	7.617
500 year	135.92	135.92	90.65	3.472	4.155	7-M2c	3.000	2.190	2.190	1.070	8.194

Straight Culvert


Inlet Elevation (invert): 86.50 ft, Outlet Elevation (invert): 86.00 ft

Culvert Length: 343.00 ft, Culvert Slope: 0.0015

Culvert Performance Curve Plot: CD-1-05 POST

Performance Curve


Culvert: CD-1-05 POST



Water Surface Profile Plot for Culvert: CD-1-05 POST

Crossing - CD-1-05 POST, Design Discharge - 135.9 cfs

Culvert - CD-1-05 POST, Culvert Discharge - 135.9 cfs



Site Data - CD-1-05 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 86.50 ft

Outlet Station: 343.00 ft

Outlet Elevation: 86.00 ft

Number of Barrels: 3

Culvert Data Summary - CD-1-05 POST

Barrel Shape: Circular

Barrel Diameter: 3.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Beveled Edge (1:1)

Inlet Depression: None

Table 15 - Downstream Channel Rating Curve (Crossing: CD-1-05 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
109.50	87.07	1.07
115.06	87.07	1.07
135.92	87.07	1.07

Tailwater Channel Data - CD-1-05 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 87.07 ft

Roadway Data for Crossing: CD-1-05 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 94.50 ft

Roadway Surface: Paved

Roadway Top Width: 172.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 16 - Summary of Culvert Flows at Crossing: CD-1-06 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-1-06 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
87.20	50 year	114.59	114.59	0.00	1
87.48	100 year	118.37	118.37	0.00	1
88.13	500 year	131.80	127.48	4.11	15
88.07	Overtopping	126.70	126.70	0.00	Overtopping

Rating Curve Plot for Crossing: CD-1-06 POST

Total Rating Curve

Crossing: CD-1-06 POST





Table 17 - Culvert Summary Table: CD-1-06 POST

Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	114.59	114.59	87.20	4.605	6.198	7-M2c	3.000	2.449	2.449	0.570	9.273
100 year	118.37	118.37	87.48	4.776	6.476	7-M2c	3.000	2.485	2.485	0.570	9.454
500 year	131.80	127.48	88.13	5.215	7.128	7-M2c	3.000	2.564	2.564	0.570	9.907

Straight Culvert
Inlet Elevation (invert): 81.00 ft, Outlet Elevation (invert): 80.83 ft
Culvert Length: 336.00 ft, Culvert Slope: 0.0005


Culvert Performance Curve Plot: CD-1-06 POST



Water Surface Profile Plot for Culvert: CD-1-06 POST

Crossing - CD-1-06 POST, Design Discharge - 131.8 cfs

Culvert - CD-1-06 POST, Culvert Discharge - 127.5 cfs



Site Data - CD-1-06 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 81.00 ft

Outlet Station: 336.00 ft

Outlet Elevation: 80.83 ft

Number of Barrels: 2

Culvert Data Summary - CD-1-06 POST

Barrel Shape: Circular

Barrel Diameter: 3.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 18 - Downstream Channel Rating Curve (Crossing: CD-1-06 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
114.59	81.57	0.57
118.37	81.57	0.57
131.80	81.57	0.57

Tailwater Channel Data - CD-1-06 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 81.57 ft

Roadway Data for Crossing: CD-1-06 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 88.07 ft

Roadway Surface: Paved

Roadway Top Width: 160.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 19 - Summary of Culvert Flows at Crossing: CD-1-07 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-1-07 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
86.36	50 year	264.98	264.98	0.00	1
87.24	100 year	294.19	294.19	0.00	1
88.71	500 year	398.06	339.39	58.36	7
88.37	Overtopping	329.73	329.73	0.00	Overtopping

Rating Curve Plot for Crossing: CD-1-07 POST

Total Rating Curve

Crossing: CD-1-07 POST




Table 20 - Culvert Summary Table: CD-1-07 POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	264.98	264.98	86.36	4.238	5.988	7-M2c	3.000	2.363	2.363	0.100	8.874
100 year	294.19	294.19	87.24	4.744	6.873	7-M2c	3.000	2.478	2.478	0.100	9.421
500 year	398.06	339.39	88.71	5.646	8.335	7-M2c	3.000	2.628	2.628	0.100	10.341

Straight Culvert
Inlet Elevation (invert): 80.37 ft, Outlet Elevation (invert): 80.27 ft
Culvert Length: 392.00 ft, Culvert Slope: 0.0003

Culvert Performance Curve Plot: CD-1-07 POST

Performance Curve


Culvert: CD-1-07 POST



Water Surface Profile Plot for Culvert: CD-1-07 POST

Crossing - CD-1-07 POST, Design Discharge - 398.1 cfs

Culvert - CD-1-07 POST, Culvert Discharge - 339.4 cfs



Site Data - CD-1-07 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 80.37 ft

Outlet Station: 392.00 ft

Outlet Elevation: 80.27 ft

Number of Barrels: 5

Culvert Data Summary - CD-1-07 POST

Barrel Shape: Circular

Barrel Diameter: 3.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 21 - Downstream Channel Rating Curve (Crossing: CD-1-07 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
264.98	80.47	0.10
294.19	80.47	0.10
398.06	80.47	0.10

Tailwater Channel Data - CD-1-07 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 80.47 ft

Roadway Data for Crossing: CD-1-07 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 88.37 ft

Roadway Surface: Paved

Roadway Top Width: 160.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 22 - Summary of Culvert Flows at Crossing: CD-1-08 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-1-08 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
76.98	50 year	106.69	106.69	0.00	1
77.22	100 year	119.51	119.51	0.00	1
78.28	500 year	165.91	165.91	0.00	1
79.77	Overtopping	214.66	214.66	0.00	Overtopping

Rating Curve Plot for Crossing: CD-1-08 POST

Total Rating Curve

Crossing: CD-1-08 POST




Table 23 - Culvert Summary Table: CD-1-08 POST

Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	106.69	106.69	76.98	2.711	6.984	4-FFf	3.167	1.816	3.167	6.070	4.177
100 year	119.51	119.51	77.22	2.930	7.217	4-FFf	3.167	1.933	3.167	6.070	4.679
500 year	165.91	165.91	78.28	3.784	8.280	4-FFf	3.167	2.305	3.167	6.070	6.496

Straight Culvert


Inlet Elevation (invert): 70.00 ft, Outlet Elevation (invert): 69.79 ft

Culvert Length: 430.00 ft, Culvert Slope: 0.0005

Culvert Performance Curve Plot: CD-1-08 POST

Performance Curve


Culvert: CD-1-08 POST



Water Surface Profile Plot for Culvert: CD-1-08 POST

Crossing - CD-1-08 POST, Design Discharge - 165.9 cfs

Culvert - CD-1-08 POST, Culvert Discharge - 165.9 cfs



Site Data - CD-1-08 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 70.00 ft

Outlet Station: 430.00 ft

Outlet Elevation: 69.79 ft

Number of Barrels: 2

Culvert Data Summary - CD-1-08 POST

Barrel Shape: Elliptical

Barrel Span: 60.00 in

Barrel Rise: 38.00 in

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 24 - Downstream Channel Rating Curve (Crossing: CD-1-08 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
106.69	76.07	6.07
119.51	76.07	6.07
165.91	76.07	6.07

Tailwater Channel Data - CD-1-08 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 76.07 ft

Roadway Data for Crossing: CD-1-08 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 79.77 ft

Roadway Surface: Paved

Roadway Top Width: 160.00 ft

Crossing Discharge Data

Discharge Selection Method: User Defined

Table 25 - Summary of Culvert Flows at Crossing: CD-4-01 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-4-01 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
81.07	EAST5WET	554.47	554.47	0.00	1
81.30	RRNORTH	584.05	584.05	0.00	1
84.00	Overtopping	860.72	860.72	0.00	Overtopping

Rating Curve Plot for Crossing: CD-4-01 POST

Total Rating Curve

Crossing: CD-4-01 POST




Table 26 - Culvert Summary Table: CD-4-01 POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
EAST5WET	554.47	554.47	81.07	3.636	5.845	4-FFf	3.167	2.250	3.167	4.000	6.203
RRNORTH	584.05	584.05	81.30	3.803	6.072	4-FFf	3.167	2.312	3.167	4.000	6.534

Straight Culvert
Inlet Elevation (invert): 75.23 ft, Outlet Elevation (invert): 75.00 ft
Culvert Length: 453.00 ft, Culvert Slope: 0.0005

Culvert Performance Curve Plot: CD-4-01 POST

Performance Curve


Culvert: CD-4-01 POST



Water Surface Profile Plot for Culvert: CD-4-01 POST

Crossing - CD-4-01 POST, Design Discharge - 584.0 cfs

Culvert - CD-4-01 POST, Culvert Discharge - 584.0 cfs



Site Data - CD-4-01 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 75.23 ft

Outlet Station: 453.00 ft

Outlet Elevation: 75.00 ft

Number of Barrels: 7

Culvert Data Summary - CD-4-01 POST

Barrel Shape: Elliptical

Barrel Span: 60.00 in

Barrel Rise: 38.00 in

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 27 - Downstream Channel Rating Curve (Crossing: CD-4-01 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
554.47	79.00	4.00
584.05	79.00	4.00

Tailwater Channel Data - CD-4-01 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 79.00 ft

Roadway Data for Crossing: CD-4-01 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 84.00 ft

Roadway Surface: Paved

Roadway Top Width: 250.00 ft

Crossing Discharge Data

Discharge Selection Method: User Defined

Table 28 - Summary of Culvert Flows at Crossing: CD-4-02 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-4-02 POST Discharge (cfs)	CD-4-02B POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
73.74	17-92SE	158.85	118.62	40.39	0.00	11
73.74	17-92SE	158.85	118.62	40.39	0.00	2
79.00	Overtopping	501.84	355.48	146.36	0.00	Overtopping

Rating Curve Plot for Crossing: CD-4-02 POST

Total Rating Curve

Crossing: CD-4-02 POST




Table 29 - Culvert Summary Table: CD-4-02 POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
17-92SE	158.85	118.62	73.74	2.742	2.473	1-JS1f	0.864	1.635	3.000	2.000	3.954
17-92SE	158.85	118.62	73.74	2.742	2.473	1-JS1f	0.864	1.635	3.000	2.000	3.954

Straight Culvert
Inlet Elevation (invert): 71.00 ft, Outlet Elevation (invert): 68.80 ft
Culvert Length: 130.02 ft, Culvert Slope: 0.0169

Culvert Performance Curve Plot: CD-4-02 POST

Performance Curve


Culvert: CD-4-02 POST



Water Surface Profile Plot for Culvert: CD-4-02 POST

Crossing - CD-4-02 POST, Design Discharge - 158.8 cfs

Culvert - CD-4-02 POST, Culvert Discharge - 118.6 cfs



Site Data - CD-4-02 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 71.00 ft

Outlet Station: 130.00 ft

Outlet Elevation: 68.80 ft

Number of Barrels: 1

Culvert Data Summary - CD-4-02 POST

Barrel Shape: Concrete Box

Barrel Span: 10.00 ft

Barrel Rise: 3.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge (90°) Headwall

Inlet Depression: None

Table 30 - Culvert Summary Table: CD-4-02B POST

Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
17-92SE	158.85	40.39	73.74	2.742	2.327	1-JS1f	1.178	1.898	4.000	2.000	3.214
17-92SE	158.85	40.39	73.74	2.742	2.327	1-JS1f	1.178	1.898	4.000	2.000	3.214

Straight Culvert


Inlet Elevation (invert): 71.00 ft, Outlet Elevation (invert): 68.80 ft

Culvert Length: 130.02 ft, Culvert Slope: 0.0169

Culvert Performance Curve Plot: CD-4-02B POST

Performance Curve


Culvert: CD-4-02B POST



Water Surface Profile Plot for Culvert: CD-4-02B POST

Crossing - CD-4-02 POST, Design Discharge - 158.8 cfs

Culvert - CD-4-02B POST, Culvert Discharge - 40.4 cfs



Site Data - CD-4-02B POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 71.00 ft

Outlet Station: 130.00 ft

Outlet Elevation: 68.80 ft

Number of Barrels: 1

Culvert Data Summary - CD-4-02B POST

Barrel Shape: Circular

Barrel Diameter: 4.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 31 - Downstream Channel Rating Curve (Crossing: CD-4-02 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
158.85	73.00	2.00
158.85	73.00	2.00

Tailwater Channel Data - CD-4-02 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 73.00 ft

Roadway Data for Crossing: CD-4-02 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 79.00 ft

Roadway Surface: Paved

Roadway Top Width: 101.00 ft

Crossing Discharge Data

Discharge Selection Method: User Defined

Table 32 - Summary of Culvert Flows at Crossing: CD-4-03 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-4-03 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
68.71	17-92NE	613.05	613.05	0.00	1
68.71	17-92NE	613.05	613.05	0.00	1
72.50	Overtopping	1109.36	1109.36	0.00	Overtopping

Rating Curve Plot for Crossing: CD-4-03 POST

Total Rating Curve

Crossing: CD-4-03 POST





Table 33 - Culvert Summary Table: CD-4-03 POST

Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
17-92NE	613.05	613.05	68.71	4.698	4.712	7-M2c	4.000	2.726	2.726	2.500	9.369
17-92NE	613.05	613.05	68.71	4.698	4.712	7-M2c	4.000	2.726	2.726	2.500	9.369


Straight Culvert
Inlet Elevation (invert): 64.00 ft, Outlet Elevation (invert): 63.90 ft
Culvert Length: 140.00 ft, Culvert Slope: 0.0007

Culvert Performance Curve Plot: CD-4-03 POST



Water Surface Profile Plot for Culvert: CD-4-03 POST

Crossing - CD-4-03 POST, Design Discharge - 613.0 cfs
Culvert - CD-4-03 POST, Culvert Discharge - 613.0 cfs



Site Data - CD-4-03 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 64.00 ft

Outlet Station: 140.00 ft

Outlet Elevation: 63.90 ft

Number of Barrels: 3

Culvert Data Summary - CD-4-03 POST

Barrel Shape: Concrete Box

Barrel Span: 8.00 ft

Barrel Rise: 4.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge (90°) Headwall

Inlet Depression: None

Table 34 - Downstream Channel Rating Curve (Crossing: CD-4-03 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
613.05	66.50	2.50
613.05	66.50	2.50

Tailwater Channel Data - CD-4-03 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 66.50 ft

Roadway Data for Crossing: CD-4-03 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 400.00 ft

Crest Elevation: 72.50 ft

Roadway Surface: Paved

Roadway Top Width: 170.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 35 - Summary of Culvert Flows at Crossing: CD-4-05A POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-4-05A POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
86.06	50 year	276.49	276.49	0.00	1
86.86	100 year	305.84	305.84	0.00	1
88.65	500 year	408.92	364.97	43.67	6
88.37	Overtopping	355.95	355.95	0.00	Overtopping

Rating Curve Plot for Crossing: CD-4-05A POST

Total Rating Curve

Crossing: CD-4-05A POST




Table 36 - Culvert Summary Table: CD-4-05A POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	276.49	276.49	86.06	3.711	5.689	7-M2c	3.000	2.209	2.209	0.100	8.261
100 year	305.84	305.84	86.86	4.076	6.486	7-M2c	3.000	2.320	2.320	0.100	8.691
500 year	408.92	364.97	88.65	4.930	8.278	7-M2c	3.000	2.514	2.514	0.100	9.615

Straight Culvert
Inlet Elevation (invert): 80.37 ft, Outlet Elevation (invert): 80.27 ft
Culvert Length: 550.00 ft, Culvert Slope: 0.0002

Culvert Performance Curve Plot: CD-4-05A POST

Performance Curve


Culvert: CD-4-05A POST



Water Surface Profile Plot for Culvert: CD-4-05A POST

Crossing - CD-4-05A POST, Design Discharge - 408.9 cfs

Culvert - CD-4-05A POST, Culvert Discharge - 365.0 cfs



Site Data - CD-4-05A POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 80.37 ft

Outlet Station: 550.00 ft

Outlet Elevation: 80.27 ft

Number of Barrels: 6

Culvert Data Summary - CD-4-05A POST

Barrel Shape: Circular

Barrel Diameter: 3.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 37 - Downstream Channel Rating Curve (Crossing: CD-4-05A POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
276.49	80.47	0.10
305.84	80.47	0.10
408.92	80.47	0.10

Tailwater Channel Data - CD-4-05A POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 80.47 ft

Roadway Data for Crossing: CD-4-05A POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 88.37 ft

Roadway Surface: Paved

Roadway Top Width: 164.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 38 - Summary of Culvert Flows at Crossing: CD-4-05B POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-4-05B POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
84.04	50 year	302.16	302.16	0.00	1
84.78	100 year	335.55	335.55	0.00	1
87.18	500 year	452.27	430.15	21.81	10
87.00	Overtopping	424.03	424.03	0.00	Overtopping

Rating Curve Plot for Crossing: CD-4-05B POST

Total Rating Curve

Crossing: CD-4-05B POST




Table 39 - Culvert Summary Table: CD-4-05B POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	302.16	302.16	84.04	4.027	5.037	7-M2c	3.000	2.306	2.306	1.470	8.636
100 year	335.55	335.55	84.78	4.483	5.776	7-M2c	3.000	2.423	2.423	1.470	9.144
500 year	452.27	430.15	87.18	6.069	8.176	7-M2c	3.000	2.679	2.679	1.470	10.759

Straight Culvert

Inlet Elevation (invert): 79.00 ft, Outlet Elevation (invert): 78.58 ft

Culvert Length: 340.00 ft, Culvert Slope: 0.0012


Culvert Performance Curve Plot: CD-4-05B POST



Water Surface Profile Plot for Culvert: CD-4-05B POST

Crossing - CD-4-05B POST, Design Discharge - 452.3 cfs

Culvert - CD-4-05B POST, Culvert Discharge - 430.2 cfs



Site Data - CD-4-05B POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 79.00 ft

Outlet Station: 340.00 ft

Outlet Elevation: 78.58 ft

Number of Barrels: 6

Culvert Data Summary - CD-4-05B POST

Barrel Shape: Circular

Barrel Diameter: 3.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 40 - Downstream Channel Rating Curve (Crossing: CD-4-05B POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
302.16	80.47	1.47
335.55	80.47	1.47
452.27	80.47	1.47

Tailwater Channel Data - CD-4-05B POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 80.47 ft

Roadway Data for Crossing: CD-4-05B POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 87.00 ft

Roadway Surface: Paved

Roadway Top Width: 152.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 41 - Summary of Culvert Flows at Crossing: CD-4-06 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-4-06 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
77.08	50 year	109.72	109.72	0.00	1
77.32	100 year	121.35	121.35	0.00	1
78.43	500 year	166.07	166.07	0.00	1
79.77	Overtopping	208.04	208.04	0.00	Overtopping

Rating Curve Plot for Crossing: CD-4-06 POST

Total Rating Curve

Crossing: CD-4-06 POST




Table 42 - Culvert Summary Table: CD-4-06 POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	109.72	109.72	77.08	2.759	3.370	3-M1f	1.947	1.847	3.167	2.360	4.296
100 year	121.35	121.35	77.32	2.959	3.612	3-M1f	2.083	1.949	3.167	2.360	4.751
500 year	166.07	166.07	78.43	3.784	4.717	4-FFf	3.167	2.307	3.167	2.360	6.502

Straight Culvert

Inlet Elevation (invert): 73.71 ft, Outlet Elevation (invert): 72.59 ft

Culvert Length: 480.00 ft, Culvert Slope: 0.0023


Culvert Performance Curve Plot: CD-4-06 POST



Water Surface Profile Plot for Culvert: CD-4-06 POST

Crossing - CD-4-06 POST, Design Discharge - 166.1 cfs

Culvert - CD-4-06 POST, Culvert Discharge - 166.1 cfs



Site Data - CD-4-06 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 73.71 ft

Outlet Station: 480.00 ft

Outlet Elevation: 72.59 ft

Number of Barrels: 2

Culvert Data Summary - CD-4-06 POST

Barrel Shape: Elliptical

Barrel Span: 60.00 in

Barrel Rise: 38.00 in

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 43 - Downstream Channel Rating Curve (Crossing: CD-4-06 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
109.72	76.07	2.36
121.35	76.07	2.36
166.07	76.07	2.36

Tailwater Channel Data - CD-4-06 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 76.07 ft

Roadway Data for Crossing: CD-4-06 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 79.77 ft

Roadway Surface: Paved

Roadway Top Width: 278.00 ft

Crossing Discharge Data

Discharge Selection Method: User Defined

Table 44 - Summary of Culvert Flows at Crossing: CD-5-01 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-5-01 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
81.07	EAST5WET	554.47	554.47	0.00	1
81.30	RRNORTH	584.05	584.05	0.00	1
84.00	Overtopping	860.72	860.72	0.00	Overtopping

Rating Curve Plot for Crossing: CD-5-01 POST

Total Rating Curve

Crossing: CD-5-01 POST




Table 45 - Culvert Summary Table: CD-5-01 POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
EAST5WET	554.47	554.47	81.07	3.636	5.845	4-FFf	3.167	2.250	3.167	4.000	6.203
RRNORTH	584.05	584.05	81.30	3.803	6.072	4-FFf	3.167	2.312	3.167	4.000	6.534

Straight Culvert
Inlet Elevation (invert): 75.23 ft, Outlet Elevation (invert): 75.00 ft
Culvert Length: 453.00 ft, Culvert Slope: 0.0005

Culvert Performance Curve Plot: CD-5-01 POST

Performance Curve


Culvert: CD-5-01 POST



Water Surface Profile Plot for Culvert: CD-5-01 POST

Crossing - CD-5-01 POST, Design Discharge - 584.0 cfs

Culvert - CD-5-01 POST, Culvert Discharge - 584.0 cfs



Site Data - CD-5-01 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 75.23 ft

Outlet Station: 453.00 ft

Outlet Elevation: 75.00 ft

Number of Barrels: 7

Culvert Data Summary - CD-5-01 POST

Barrel Shape: Elliptical

Barrel Span: 60.00 in

Barrel Rise: 38.00 in

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 46 - Downstream Channel Rating Curve (Crossing: CD-5-01 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
554.47	79.00	4.00
584.05	79.00	4.00

Tailwater Channel Data - CD-5-01 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 79.00 ft

Roadway Data for Crossing: CD-5-01 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 84.00 ft

Roadway Surface: Paved

Roadway Top Width: 250.00 ft

Crossing Discharge Data

Discharge Selection Method: User Defined

Table 47 - Summary of Culvert Flows at Crossing: CD-5-02 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-5-02 POST Discharge (cfs)	CD-5-02B POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
73.74	17-92SE	158.85	118.62	40.39	0.00	11
73.74	17-92SE	158.85	118.62	40.39	0.00	2
79.00	Overtopping	501.84	355.48	146.36	0.00	Overtopping

Rating Curve Plot for Crossing: CD-5-02 POST

Total Rating Curve

Crossing: CD-5-02 POST




Table 48 - Culvert Summary Table: CD-5-02 POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
17-92SE	158.85	118.62	73.74	2.742	2.473	1-JS1f	0.864	1.635	3.000	2.000	3.954
17-92SE	158.85	118.62	73.74	2.742	2.473	1-JS1f	0.864	1.635	3.000	2.000	3.954

Straight Culvert

Inlet Elevation (invert): 71.00 ft, Outlet Elevation (invert): 68.80 ft

Culvert Length: 130.02 ft, Culvert Slope: 0.0169


Culvert Performance Curve Plot: CD-5-02 POST



Water Surface Profile Plot for Culvert: CD-5-02 POST

Crossing - CD-5-02 POST, Design Discharge - 158.8 cfs

Culvert - CD-5-02 POST, Culvert Discharge - 118.6 cfs



Site Data - CD-5-02 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 71.00 ft

Outlet Station: 130.00 ft

Outlet Elevation: 68.80 ft

Number of Barrels: 1

Culvert Data Summary - CD-5-02 POST

Barrel Shape: Concrete Box

Barrel Span: 10.00 ft

Barrel Rise: 3.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge (90°) Headwall

Inlet Depression: None

Table 49 - Culvert Summary Table: CD-5-02B POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
17-92SE	158.85	40.39	73.74	2.742	2.327	1-JS1f	1.178	1.898	4.000	2.000	3.214
17-92SE	158.85	40.39	73.74	2.742	2.327	1-JS1f	1.178	1.898	4.000	2.000	3.214

Straight Culvert
Inlet Elevation (invert): 71.00 ft, Outlet Elevation (invert): 68.80 ft
Culvert Length: 130.02 ft, Culvert Slope: 0.0169

Culvert Performance Curve Plot: CD-5-02B POST

Performance Curve


Culvert: CD-5-02B POST



Water Surface Profile Plot for Culvert: CD-5-02B POST

Crossing - CD-5-02 POST, Design Discharge - 158.8 cfs

Culvert - CD-5-02B POST, Culvert Discharge - 40.4 cfs



Site Data - CD-5-02B POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 71.00 ft

Outlet Station: 130.00 ft

Outlet Elevation: 68.80 ft

Number of Barrels: 1

Culvert Data Summary - CD-5-02B POST

Barrel Shape: Circular

Barrel Diameter: 4.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 50 - Downstream Channel Rating Curve (Crossing: CD-5-02 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
158.85	73.00	2.00
158.85	73.00	2.00

Tailwater Channel Data - CD-5-02 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 73.00 ft

Roadway Data for Crossing: CD-5-02 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 79.00 ft

Roadway Surface: Paved

Roadway Top Width: 101.00 ft

Crossing Discharge Data

Discharge Selection Method: User Defined

Table 51 - Summary of Culvert Flows at Crossing: CD-5-03 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-5-03 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
68.71	17-92NE	613.05	613.05	0.00	1
68.71	17-92NE	613.05	613.05	0.00	1
72.50	Overtopping	1109.36	1109.36	0.00	Overtopping

Rating Curve Plot for Crossing: CD-5-03 POST

Total Rating Curve

Crossing: CD-5-03 POST




Table 52 - Culvert Summary Table: CD-5-03 POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
17-92NE	613.05	613.05	68.71	4.698	4.712	7-M2c	4.000	2.726	2.726	2.500	9.369
17-92NE	613.05	613.05	68.71	4.698	4.712	7-M2c	4.000	2.726	2.726	2.500	9.369

Straight Culvert

Inlet Elevation (invert): 64.00 ft, Outlet Elevation (invert): 63.90 ft

Culvert Length: 140.00 ft, Culvert Slope: 0.0007


Culvert Performance Curve Plot: CD-5-03 POST



Water Surface Profile Plot for Culvert: CD-5-03 POST

Crossing - CD-5-03 POST, Design Discharge - 613.0 cfs

Culvert - CD-5-03 POST, Culvert Discharge - 613.0 cfs



Site Data - CD-5-03 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 64.00 ft

Outlet Station: 140.00 ft

Outlet Elevation: 63.90 ft

Number of Barrels: 3

Culvert Data Summary - CD-5-03 POST

Barrel Shape: Concrete Box

Barrel Span: 8.00 ft

Barrel Rise: 4.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge (90°) Headwall

Inlet Depression: None

Table 53 - Downstream Channel Rating Curve (Crossing: CD-5-03 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
613.05	66.50	2.50
613.05	66.50	2.50

Tailwater Channel Data - CD-5-03 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 66.50 ft

Roadway Data for Crossing: CD-5-03 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 400.00 ft

Crest Elevation: 72.50 ft

Roadway Surface: Paved

Roadway Top Width: 170.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 54 - Summary of Culvert Flows at Crossing: CD-5-05A POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-5-05A POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
86.75	50 year	276.39	276.39	0.00	1
87.66	100 year	303.37	303.37	0.00	1
88.74	500 year	401.83	333.14	68.52	6
88.37	Overtopping	323.23	323.23	0.00	Overtopping

Rating Curve Plot for Crossing: CD-5-05A POST

Total Rating Curve

Crossing: CD-5-05A POST




Table 55 - Culvert Summary Table: CD-5-05A POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	276.39	276.39	86.75	5.774	6.383	7-M2c	3.000	2.645	2.645	0.100	10.473
100 year	303.37	303.37	87.66	6.556	7.293	7-M2c	3.000	2.729	2.729	0.100	11.233
500 year	401.83	333.14	88.74	7.509	8.374	7-M2c	3.000	2.801	2.801	0.100	12.128

Straight Culvert

Inlet Elevation (invert): 80.37 ft, Outlet Elevation (invert): 79.68 ft

Culvert Length: 220.00 ft, Culvert Slope: 0.0031


Culvert Performance Curve Plot: CD-5-05A POST



Water Surface Profile Plot for Culvert: CD-5-05A POST

Crossing - CD-5-05A POST, Design Discharge - 401.8 cfs

Culvert - CD-5-05A POST, Culvert Discharge - 333.1 cfs



Site Data - CD-5-05A POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 80.37 ft

Outlet Station: 220.00 ft

Outlet Elevation: 79.68 ft

Number of Barrels: 4

Culvert Data Summary - CD-5-05A POST

Barrel Shape: Circular

Barrel Diameter: 3.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 56 - Downstream Channel Rating Curve (Crossing: CD-5-05A POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
276.39	80.47	0.10
303.37	80.47	0.10
401.83	80.47	0.10

Tailwater Channel Data - CD-5-05A POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 80.47 ft

Roadway Data for Crossing: CD-5-05A POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 88.37 ft

Roadway Surface: Paved

Roadway Top Width: 80.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 57 - Summary of Culvert Flows at Crossing: CD-5-05B POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-5-05B POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
85.54	50 year	355.42	355.42	0.00	1
86.51	100 year	394.84	394.84	0.00	1
87.49	500 year	536.62	431.15	105.20	3
87.00	Overtopping	413.09	413.09	0.00	Overtopping

Rating Curve Plot for Crossing: CD-5-05B POST

Total Rating Curve

Crossing: CD-5-05B POST




Table 58 - Culvert Summary Table: CD-5-05B POST


Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	355.42	355.42	85.54	4.781	6.536	7-M2c	3.000	2.486	2.486	1.470	9.459
100 year	394.84	394.84	86.51	5.426	7.511	7-M2c	3.000	2.597	2.597	1.470	10.121
500 year	536.62	431.15	87.49	6.089	8.494	7-M2c	3.000	2.682	2.682	1.470	10.778

Straight Culvert

Inlet Elevation (invert): 79.00 ft, Outlet Elevation (invert): 78.83 ft

Culvert Length: 344.00 ft, Culvert Slope: 0.0005


Culvert Performance Curve Plot: CD-5-05B POST



Water Surface Profile Plot for Culvert: CD-5-05B POST

Crossing - CD-5-05B POST, Design Discharge - 536.6 cfs

Culvert - CD-5-05B POST, Culvert Discharge - 431.2 cfs



Site Data - CD-5-05B POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 79.00 ft

Outlet Station: 344.00 ft

Outlet Elevation: 78.83 ft

Number of Barrels: 6

Culvert Data Summary - CD-5-05B POST

Barrel Shape: Circular

Barrel Diameter: 3.00 ft

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 59 - Downstream Channel Rating Curve (Crossing: CD-5-05B POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
355.42	80.47	1.47
394.84	80.47	1.47
536.62	80.47	1.47

Tailwater Channel Data - CD-5-05B POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 80.47 ft

Roadway Data for Crossing: CD-5-05B POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 87.00 ft

Roadway Surface: Paved

Roadway Top Width: 154.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 60 - Summary of Culvert Flows at Crossing: CD-5-06 POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-5-06 POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
77.58	50 year	110.32	110.32	0.00	1
77.58	100 year	110.32	110.32	0.00	1
79.75	500 year	172.55	172.55	0.00	1
79.77	Overtopping	172.92	172.92	0.00	Overtopping

Rating Curve Plot for Crossing: CD-5-06 POST

Total Rating Curve

Crossing: CD-5-06 POST




Table 61 - Culvert Summary Table: CD-5-06 POST

Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	110.32	110.32	77.58	2.771	3.866	4-FFf	2.405	1.852	3.167	2.360	4.319
100 year	110.32	110.32	77.58	2.771	3.866	4-FFf	2.405	1.852	3.167	2.360	4.319
500 year	172.55	172.55	79.75	3.917	6.044	4-FFf	3.167	2.353	3.167	2.360	6.756

Straight Culvert


Inlet Elevation (invert): 73.71 ft, Outlet Elevation (invert): 72.59 ft

Culvert Length: 849.00 ft, Culvert Slope: 0.0013

Culvert Performance Curve Plot: CD-5-06 POST

Performance Curve


Culvert: CD-5-06 POST



Water Surface Profile Plot for Culvert: CD-5-06 POST

Crossing - CD-5-06 POST, Design Discharge - 172.6 cfs

Culvert - CD-5-06 POST, Culvert Discharge - 172.6 cfs



Site Data - CD-5-06 POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 73.71 ft

Outlet Station: 849.00 ft

Outlet Elevation: 72.59 ft

Number of Barrels: 2

Culvert Data Summary - CD-5-06 POST

Barrel Shape: Elliptical

Barrel Span: 60.00 in

Barrel Rise: 38.00 in

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 62 - Downstream Channel Rating Curve (Crossing: CD-5-06 POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
110.32	76.07	2.36
110.32	76.07	2.36
172.55	76.07	2.36

Tailwater Channel Data - CD-5-06 POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 76.07 ft

Roadway Data for Crossing: CD-5-06 POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 79.77 ft

Roadway Surface: Paved

Roadway Top Width: 610.00 ft

Crossing Discharge Data

Discharge Selection Method: Recurrence

Table 63 - Summary of Culvert Flows at Crossing: CD-5B-05B POST

Headwater Elevation (ft)	Discharge Names	Total Discharge (cfs)	CD-5B-05B POST Discharge (cfs)	Roadway Discharge (cfs)	Iterations
77.33	50 year	134.26	134.26	0.00	1
77.55	100 year	145.21	145.21	0.00	1
78.76	500 year	195.45	195.45	0.00	1
79.77	Overtopping	229.18	229.18	0.00	Overtopping

Rating Curve Plot for Crossing: CD-5B-05B POST

Total Rating Curve

Crossing: CD-5B-05B POST





Table 64 - Culvert Summary Table: CD-5B-05B POST

Discharge Names	Total Discharge (cfs)	Culvert Discharge (cfs)	Headwater Elevation (ft)	Inlet Control Depth (ft)	Outlet Control Depth (ft)	Flow Type	Normal Depth (ft)	Critical Depth (ft)	Outlet Depth (ft)	Tailwater Depth (ft)	Outlet Velocity (ft/s)
50 year	134.26	134.26	77.33	3.184	3.628	1-S1f	1.981	2.057	3.167	2.370	5.257
100 year	145.21	145.21	77.55	3.382	3.852	1-S1f	2.089	2.149	3.167	2.370	5.686
500 year	195.45	195.45	78.76	4.412	5.061	4-FFf	3.167	2.507	3.167	2.370	7.653

Straight Culvert
Inlet Elevation (invert): 73.70 ft, Outlet Elevation (invert): 72.59 ft
Culvert Length: 335.00 ft, Culvert Slope: 0.0033


Culvert Performance Curve Plot: CD-5B-05B POST



Water Surface Profile Plot for Culvert: CD-5B-05B POST

Crossing - CD-5B-05B POST, Design Discharge - 195.4 cfs

Culvert - CD-5B-05B POST, Culvert Discharge - 195.4 cfs



Site Data - CD-5B-05B POST

Site Data Option: Culvert Invert Data

Inlet Station: 0.00 ft

Inlet Elevation: 73.70 ft

Outlet Station: 335.00 ft

Outlet Elevation: 72.59 ft

Number of Barrels: 2

Culvert Data Summary - CD-5B-05B POST

Barrel Shape: Elliptical

Barrel Span: 60.00 in

Barrel Rise: 38.00 in

Barrel Material: Concrete

Embedment: 0.00 in

Barrel Manning's n: 0.0120

Culvert Type: Straight

Inlet Configuration: Square Edge with Headwall

Inlet Depression: None

Table 65 - Downstream Channel Rating Curve (Crossing: CD-5B-05B POST)

Flow (cfs)	Water Surface Elev (ft)	Depth (ft)
134.26	76.07	2.37
145.21	76.07	2.37
195.45	76.07	2.37

Tailwater Channel Data - CD-5B-05B POST

Tailwater Channel Option: Enter Constant Tailwater Elevation

Constant Tailwater Elevation: 76.07 ft

Roadway Data for Crossing: CD-5B-05B POST

Roadway Profile Shape: Constant Roadway Elevation

Crest Length: 100.00 ft

Crest Elevation: 79.77 ft

Roadway Surface: Paved

Roadway Top Width: 142.00 ft